



172+54 Lt  
Relocate Mailbox -  
Single Support

172+50 ~ 175+00 RT  
NEW 6" x 250' UNDERDRAIN  
W/ FB @ 175+00 RT

EXISTING PAVEMENT (9") x (22' WIDE) @ (16.5%)

172+50 E  
REMOVE EXISTING 18" ACCOMP

1/2" Bit.  
Conc. Pavement

470

\* 3" Subbase of Crushed Gravel  
(Fine Graded) over 9" Dense  
Graded Crushed Stone

Section  
A-A

172+00 Lt ~ 172+50 RT  
NEW 24" x 92' PCCSP (064), CPED (54), OR  
CAAP (060) W/ STONE FILL, TYPE I @  
OUTLET

172+25 RT  
CONSTRUCT DRIVE (Paved)

172+00 Rt  
Combs pole  
240  
205

STONE FILL, TYPE I  
6' WIDE

EXISTING PAVEMENT (9") x (22' WIDE AVERAGE @ (16.5%))

EXISTING PAVEMENT (9") x (22' WIDE AVERAGE @ (16.5%))

470

470

470

470

FROM STA. 171+50	TO STA. 172+75
PROJECT NAME MORETOWN	
NO. 2526	RS0167 (9)
SURVEYED BY MOREAU	PLOTTED 04/15/87
SHEET 78	01/86 0039
OF 243 SHEETS	

SCALE 10 FEET