



Benchmark #3  
RR Spike in Root  
Elev. ~~223.213~~  
223.247

Manufactured Terminal Section, Flared  
10+095.00 ~ 10+106.40 Lt.

Bituminous Concrete Curb, Type A  
10+085.00 ~ 10+120.00 Lt.

Removal and Disposal of Guardrail  
10+095.70 - 10+098.70 Lt.  
10+098.70 - 10+120.00 Rt.

HD SteelBeam Guardrail, Galvanized w/ 2.4m Posts  
9+970.00 ~ 9+992.30 Lt.

HD SteelBeam Guardrail, Galvanized  
9+992.30 ~ 10+120.00 Lt.  
10+106.40 ~ 10+120.00 Rt.

Construct Grass Lined Channel  
10+015.00 ~ 10+084.35 Lt.

**BEGIN APPROACH**  
STA. 9+980.000

**BEGIN PROJECT**  
**END APPROACH**  
STA. 10+020.000

SEE DRAINAGE DETAIL SHEET  
FOR DRAINAGE FLAG DESCRIPTIONS

**LAYOUT 2**



PROJECT NAME:	STOCKBRIDGE
PROJECT NUMBER:	BRF 022-1 (20)
FILE NAME:	85e039/de039bdr.dgn
PROJECT LEADER:	C.P. Williams
DESIGNED BY:	R.S. YOUNG
LAYOUT 2	
PLOT DATE:	08-APR-2010
DRAWN BY:	H. I. SALLS
CHECKED BY:	R.S. Young
SHEET	16 OF 139