

# TRAFFIC SIGN SUMMARY SHEET 1



MILEMARKER, STATION, OR SIGN NUMBER	SIGN LEGEND	SIGN DIMENSIONS		NEW & SALVAGED SIGNS				EXIST POST	NO. OF POSTS	NEW SIGN POSTS												REMARKS	SIGN DETAIL					
		EA	WIDTH (mm)	HEIGHT (mm)	"A"	"B"	SALV SIGN			SALV TIS	SQUARE STEEL (mm)				TUBULAR ALUMINUM dia.(mm)			TUBULAR STEEL dia.(mm)					W-SHAPE STEEL		DETAIL ON SHEET NUMBER	STD. SHEET NUMBER		
											44	50	63	ANCHOR	S	L	E	FOUND-ATION	75	89	100		125	FTG. SIZE			WEIGHT	POST SIZE
											kg/m	kg/m	kg/m						kg/m	600 mm	750 mm							
U.S. ROUTE 2 STA. 18+454.9, LT.		1	600	750	0.45				1	4.2	1														R2-I(40)	SHS		
STA. 18+462.8, RT.		1	600	750	0.45				1	4.2	1														R2-I(30)	SHS		
STA. 18+494.5, RT.		1	750	750	0.56				1	4.2	1														VW-060	E-154		
STA. 18+509.1, RT.		1	900	900	0.81				2	8.7	2														S1-1 (FYG) S4-3 (FYG)	SHS SHS		
STA. 18+526.5, RT.							3		2	8.7	2														NON-PARTICIPATING	E-125		
STA. 18+570.3, RT.		1	600	750	0.45				1	4.4	1														R4-7	SHS		
		1	450	450	0.20																				OMI-I(PLACED BACK TO BACK BELOW KEEP RIGHT SIGN)	SHS		
		1	450	450	0.20																				OMI-I(PLACED BACK TO BACK BELOW KEEP RIGHT SIGN)	SHS		
STA. 18+589.7, RT.		1	600	750	0.45				1	4.4	1														R4-7	SHS		
		1	450	450	0.20																				OMI-I(PLACED BACK TO BACK BELOW KEEP RIGHT SIGN)	SHS		
		1	450	450	0.20																				OMI-I(PLACED BACK TO BACK BELOW KEEP RIGHT SIGN)	SHS		
STA. 18+620.4, RT.		1	600	1220	0.73				2	8.7	2														INSTALL (2) FLASHING BEACONS AS DETAILED ON VTrans STANDARDS E-106M & E-175M S5-1(FYG)	SHS		
STA. 18+620.4, LT.		1	600	750	0.45				2	9.3	2														R2-I(30)	SHS		
		1	600	750	0.45																				S5-2	SHS		
STA. 18+724.4, RT.		1	150	250	0.04				1	3.4	1																E-138	
STA. 18+738.5, L.T.		1	150	250	0.04				1	3.4	1																E-138	
STA. 18+741.4, L.T.		1	750	750	0.56				1	4.2	1														W11-6H	E-153		

**NOTES:**  
1. FINAL POST LENGTHS ARE TO BE DETERMINED IN THE FIELD. POST SIZES ARE COMPUTED BASED ON INFORMATION FURNISHED ON THE STANDARD SHEETS AND THE VTRANS "SIGN POST DESIGN GUIDELINE."  
2. ALL OVERHEAD GUIDE SIGNS SHALL HAVE A MINIMUM TYPE IX LEGEND ON TYPE IX BACKGROUND. ALL GROUND MOUNTED GUIDE SIGNS SHALL HAVE A MINIMUM TYPE IX LEGEND ON TYPE III BACKGROUND. ALL CHEVRON SIGNS SHALL HAVE TYPE IX SHEETING. ALL OTHER GROUND MOUNTED SIGNS SHALL HAVE A MINIMUM TYPE III SHEETING.

<b>SHEET TOTALS</b>	m <sup>2</sup> 6.42	m <sup>2</sup>	EA. 3 (NP)	m <sup>2</sup>		m 67.8	EA.	kg	EA.	kg	EA.	EA.	kg	FYG = FLUORESCENT YELLOW GREEN	
---------------------	------------------------	----------------	---------------	----------------	--	-----------	-----	----	-----	----	-----	-----	----	--------------------------------	--

PROJECT NAME: DANVILLE  
PROJECT NUMBER: F EGC 028-3(32)  
FILE NAME: ...traffic sign summary.ptf PLOT DATE: 1/18/2011  
DESIGN SUPERVISOR: GARY SANTY DRAWN BY: STANTEC  
DESIGNED BY: STANTEC CHECKED BY: STANTEC  
TRAFFIC SIGN SUMMARY SHEET TSS-1 SHEET 156 OF 306