

ITEM DETAIL SUMMARY SHEET



LOCATION			GUARD RAIL										DROP INLETS			DRAINAGE				MISCELLANEOUS				REMARKS
			621.20	621.20	621.54	621.60	621.75	621.76	621.77	621.80	621.81				NEW PIPE			203.15	203.16	301.28	618.10			
STATION	STATION	POS.	WOOD POST G.R.	STEEL POST G.R.	2.4 m STEEL POST G.R.	WOOD POST M.E.L.T.	ANCHOR FOR G.R.	REMOVE & RESET G.R.	REPLACE G.R. POST ASSEMBLY	REPLACE BEAM UNIT	REMOVE & DISP. G.R.	REMOVE & DISP. G.P.	CHANGE ELEV. D.I.	REHAB. D.I.	GRATE/TYPE	DIA.	LENGTH	THICK. OF PIPE	STONE FILL/TYPE	COMMON EXCAVATION	SOLID ROCK EXCAVATION	SUBBASE OF CRUSHED GRAVEL	P.C.C. SIDEWALK 125 mm	
			m.	m.	m.	EA	EA	m.	EA	EA	m	EA	EA	EA		mm.	m.			m ³	m ³	t.	m ²	
7+086.0	7+189.0	RT				1			12	6	12.0													REMOVE EXISTING 4.8 m RADIUS AND ANCHOR AND INSTALL NEW MELT AT STA. 7+086.0
7+124.4	7+192.8	LT				2		68.4				12.6												INSTALL NEW MELT AT STA. 7+124.4 & STA. 7+192.8
7+748.0		RT																						
7+391.0	7+840.0	LT							18	6														
7+926.0	7+975.0	RT							4	2														
8+046.3	8+104.5	LT			58.2		2					57.5												SEE VAOT STANDARD SHEET G-1D. PROVIDE ANCHOR AT STA. 8+048.8 & STA. 8+102.0
8+125.1	8+129.5	LT		4.4			1					4.4												SEE VAOT STANDARD SHEET G-1D. PROVIDE ANCHOR AT STA. 8+127.6
8+131.6	8+136.0	RT		4.4			1					4.4												SEE VAOT STANDARD SHEET G-1D. PROVIDE ANCHOR AT STA. 8+134.1
8+157.0	8+170.0	RT							2	1														
8+248.0		LT																						
SHEET SUBTOTAL			8.8	58.2		3	4	68.4	36	15	90.9	2												
SHEET 30 SUBTOTAL			238.0	95.0		9	4	7.6	-	-	404.3	12												
ROUNDING			13.2	6.8		-	-	4.0	-	-	24.8	-												
TOTAL			260.0	160.0		12	8	80.0	36	15	520.0	14												

DATUM
 VERTICAL N/A
 HORIZONTAL N/A

ITEM DETAIL SHEET 2

SURVEYED BY N/A DATE N/A
 DRAWN BY E.C.D. DATE 11/97
 SQUAD LEADER T.P.K.
 DESIGN FILE NO. /pave/95b022/pb022.dgn
 IPARM FILE pb0221021 DATE PLOTTED 20-JAN-1998
 PROJ. NAME DORSET
 PROJ. NO. STP 9604(IIS)
 SHEET 31 OF 43 SHEETS