

PRELIMINARY INFORMATION SHEET



INDEX OF SHEETS

1.	TITLE SHEET
2.	PRELIMINARY INFORMATION SHEET
3.	PROJECT TYPICAL SHEET
4-6.	QUANTITY SHEETS
6-7.	PHASE CONSTRUCTION DETAILS
8.	TIE SHEET
9.	LAYOUT SHEET
10-11.	PROFILE AND BANKING DIAGRAM SHEETS
12-15.	PHASE CONSTRUCTION LAYOUT SIGNS AND PAVEMENT MARKINGS
16 A & B	CONSTRUCTION APPROACH AND DETOUR SIGNING
THRU 22E	DETOUR SIGN SUMMARY SHEETS
23.	TRAFFIC SIGN SUMMARY SHEET
24-27.	CONSTRUCTION SIGN DETAIL SHEETS
28.	DRAINAGE AND UTILITIES LAYOUT SHEET
29.	DRAINAGE DETAIL SHEET
30.	STREET LIGHTING LAYOUT
31.	PLAN AND ELEVATION
32.	PROJECT NOTES
33.	BRIDGE TYPICAL SECTION
34.	DECK REINFORCING PLAN
35.	LIGHT POST BASE DETAILS
36.	MISCELLANEOUS PROJECT DETAILS
37.	FRAMING PLAN
38.	STEEL GIRDER DETAILS
39.	DIAPHRAGM DETAILS
40.	KICKER BEAM DETAILS
41.	KICKER BEAM DIAPHRAGM DETAILS
42.	TELEPHONE UTILITY DETAILS
43.	WATER MAIN CROSSING PLAN AND DETAILS
44.	FIXED BEARING DETAILS ABUTMENT NO. 1
45.	EXPANSION BEARING DETAILS ABUTMENT NO. 2
46.	KICKER BEAM BEARING DETAILS
47.	RAIL LAYOUT SHEET
48.	BRIDGE RAIL DETAILS
49-51.	ORNAMENTAL RAIL DETAILS
52.	ABUTMENT NO. 1 DETAILS
53.	ABUTMENT NO. 2 DETAILS
54.	ABUTMENT TYPICAL SECTIONS
55.	JUNCTION BOX DETAILS
56.	DETAILS FOR PORTLAND CEMENT CONCRETE SIDEWALK, 200mm (MOD.)
57.	REINFORCING STEEL SCHEDULE
58.	RESOURCE SHEET
59.	MATERIAL TRANSITION & COLD PLANING DETAILS
60.	DRAINAGE PIPE PROFILES
61-64.	MAIN ST. CROSS SECTIONS
65-67.	MAINLINE 2 CROSS SECTIONS
68-71.	CHANNEL CROSS SECTIONS

LIST OF STANDARDS

C-1M	CURBS, BITUMINOUS CONCRETE SIDEWALKS GRANITE SLOPE EDGING, VERTICAL GRANITE CURB PRECAST REINFORCED CONCRETE CURB CAST IN PLACE CONCRETE CURB BITUMINOUS CONCRETE CURB, TREATED TIMBER CURB SIDEWALK RAMPES	01/03/2000
C-3M		01/03/2000
D-8M	REINF. CONCRETE DROP INLET W/GRATE (DITCHES)	08/13/1997
D-11M	GRATES & COVERS (TYPE A)	08/13/1997
D-15M	PRECAST REINF. CONC. MANHOLE GRATES (BICYCLE S CAST IRON GRATE WITH FRAME, TYPE D CAST IRON GRATE WITH FRAME, TYPE E	08/13/1997
E-100M	CONSTRUCTION APPROACH SIGNS	08/13/1997
E-101M	CONSTRUCTION SIGN DETAILS	08/13/1997
E-102M	CONSTRUCTION SIGN DETAILS	08/13/1997
E-102AM	CONSTRUCTION SIGN DETAILS	08/13/1997
E-103M	TRAFFIC CONTROL - MISCELLANEOUS DETAILS	08/13/1997
E-107M	DELINEATION, BARRICADES AND DETOURS FOR U-TURNS ON DIVIDED HIGHWAY	08/13/1997
E-107AM	BREAKAWAY BARRICADE DETAILS	06/13/1997
E-121M	STANDARD SIGN PLACEMENT - CONVENTIONAL ROAD	06/13/1997
E-123M	GUIDE SIGN PLACEMENT - MISCELLANEOUS DETAILS	08/13/1997
E-135M	INTERSTATE ROUTE MARKER SIGN DETAIL	06/13/1997
E-136AM	U.S. ROUTE MARKER SIGN DETAILS	06/13/1997
E-136BM	STATE ROUTE MARKER SIGN DETAILS	06/13/1997
E-136CM	STATE NUMBERED TOWN HIGHWAY SIGN DETAILS	06/13/1997
E-140M	REGULATORY SIGN DETAILS	06/13/1997
E-143M	REGULATORY SIGN DETAILS	06/13/1997
E-152M	WARNING SIGN DETAILS	08/13/1997
E-180M	FLANGED CHANNEL STEEL SIGN POST	06/13/1997
E-163M	TUBULAR STEEL SIGN POST	06/13/1997
E-173M	PULL BOXES AND JUNCTION BOXES	06/13/1997
E-175M	POWER DROP STANCHIONS	06/13/1997
E-180AM	STREET LIGHTING DETAILS	06/13/1997
E-180BM	STREET LIGHTING DETAILS	06/13/1997
E-181M	TYPICAL BRIDGE MOUNTING DETAILS FOR STREET LIG	08/13/1997
E-191M	PAVEMENT MARKING DETAILS	02/01/2000
E-193M	PAVEMENT MARKING DETAILS	06/13/1997
T-1M	TEMPORARY EROSION CONTROL DETAILS	08/13/1997
T-2M	TEMPORARY EROSION CONTROL DETAILS	06/13/1997

FINAL HYDRAULIC REPORT

HYDROLOGIC DATA Date: March 1, 2001

DRAINAGE AREA: 72.5 sq. km

CHARACTER OF TERRAIN: Hilly, forested upland, developed suburban & urban lowlands

STREAM CHARACTERISTICS: Perennial, non-alluvial, sinuous, not braided or anabranching

NATURE OF STREAMBED: Ledge with some gravel and cobble deposits

PEAK FLOW DATA

Q 3.33 =	42 cms	Q 50 =	191 cms
Q 10 =	98 cms	Q 100 =	224 cms
Q 25 =	142 cms	Q 500 =	348 cms

DATE OF FLOOD OF RECORD: Unknown

ESTIMATED DISCHARGE: Unknown

WATER SURFACE ELEV.: Unknown

NATURAL STREAM VELOCITY: @ Q50 = Unknown

ICE CONDITIONS: Moderate

DEBRIS: Moderate

DOES THE STREAM REACH MAXIMUM HIGHWATER ELEV. RAPIDLY? No

IS ORDINARY RISE RAPID? No

IS STAGE AFFECTED BY UPSTREAM OR DOWNSTREAM CONDITIONS? No

IF YES, DESCRIBE:

WATERSHED STORAGE: 1% HEADWATERS:

UNIFORM: X

IMMEDIATELY ABOVE SITE:

EXISTING STRUCTURE INFORMATION

STRUCTURE TYPE: Single-span steel girder bridge

YEAR BUILT: 1938

CLEAR SPAN(NORMAL TO STREAM): 15.1 m

VERTICAL CLEARANCE ABOVE STREAMBED: 4.6 m (Ave. low beam @ 76.3 m)

WATERWAY OF FULL OPENING: 85 sq. m

DISPOSITION OF STRUCTURE: Re-using abutments in rehabilitation

TYPE OF MATERIAL UNDER SUBSTRUCTURE: Ledge

WATER SURFACE ELEVATIONS AT:

Q2.33 =	Unknown	VELOCITY =	Unknown
Q10 =	72.8 m*	"	Unknown
Q25 =	Unknown	"	Unknown
Q50 =	73.5 m*	"	Unknown
Q100 =	74.0 m*	"	Unknown

LONG TERM STREAMBED CHANGES: None noted

IS THE ROADWAY OVERTOPPED BELOW Q100: No

FREQUENCY: > Q100

RELIEF ELEVATION: 77.4 m

DISCHARGE OVER ROAD @Q100: None

UPSTREAM STRUCTURE

TOWN: Brattleboro DISTANCE: 426 m

HIGHWAY #: TH 438 (FAU Elm St) STRUCTURE #: Br #32

CLEAR SPAN: 25.9 m CLEAR HEIGHT: 4.6 m

YEAR BUILT: 1989 FULL WATERWAY: Unknown

STRUCTURE TYPE: Single-span prestressed concrete box girder bridge

DOWNSTREAM STRUCTURE

TOWN: Brattleboro DISTANCE: 90 m

HIGHWAY #: Railroad STRUCTURE #: Unknown

CLEAR SPAN: Unknown CLEAR HEIGHT: Unknown

YEAR BUILT: Unknown FULL WATERWAY: Unknown

STRUCTURE TYPE: Stone and concrete arch bridge

LOAD FACTOR LOAD RATING (TONS)

LOADING LEVELS	TRUCK					
	M	MS	3S2	5A. STR.	3A. STR.	SA. SEMI
INVENTORY	35	43				
POSTED	49	60	80	54	55	68
OPERATING	71	85	110	64	66	

COMMENTS: SERVICEABILITY GOVERNS

TRAFFIC DATA

YEAR	ADT	DHV	% D	% T	ADTT
1999	15260	1525	54	2	785
2019	19730	1975	54	2	960

20 year EBAL for flexible pavement: 1999 to 2019 : 7,338,000

40 year EBAL for flexible pavement: 1999 to 2039 : 22,496,000

Design Speed: 40 km/h

PROPOSED STRUCTURE

STRUCTURE TYPE: Single-span steel girder bridge

CLEAR SPAN(NORMAL TO STREAM): 15.1 m

VERTICAL CLEARANCE ABOVE STREAMBED: 5.1 m

WATERWAY OF FULL OPENING: 73 sq. m

WATER SURFACE ELEVATIONS AT:

Q2.33 =	Unknown	VELOCITY =	Unknown
Q10 =	72.8 m*	"	Unknown
Q25 =	Unknown	"	Unknown
Q50 =	73.5 m*	"	Unknown
Q100 =	74.0 m*	"	Unknown

IS THE ROADWAY OVERTOPPED BELOW Q100: No

FREQUENCY: > Q100

RELIEF ELEVATION: 77.4 m

DISCHARGE OVER ROAD @Q100: None

AVERAGE LOW ELEVATION OF SUPERSTRUCTURE: 75.6 m

VERTICAL CLEARANCE: @ Q50 = 2.3 m

SCOUR: None, Channel bottom & Abutments on Ledge

REQUIRED CHANNEL PROTECTION: N/A

PERMIT INFORMATION

AVERAGE DAILY FLOW: 2 cms DEPTH OR ELEVATION:

ORDINARY LOW WATER: 1 cms 0.3 m

ORDINARY HIGH WATER: 18 cms 0.6 m

TEMPORARY BRIDGE REQUIREMENTS

STRUCTURE TYPE: N/A

CLEAR SPAN (NORMAL TO STREAM): N/A

VERTICAL CLEARANCE ABOVE STREAMBED: N/A

WATERWAY AREA OF FULL OPENING: N/A

ADDITIONAL INFORMATION

* Water Surface Elevations taken from FEMA Flood Insurance Study for the Town of Brattleboro, Dated Dec. 4, 1985

Note: A detailed hydraulic analysis was not performed due to limited survey and the fact that this is a rehabilitation of a hydraulically adequate bridge with no new adverse hydraulic conditions.

DESIGN CRITERIA

- DESIGN LIVE LOAD AASHTO: MS 22.5
- DESIGN SPAN: 19m ALONG CENTERLINE U.S. 5
- ALLOWABLE LOAD FOR SPREAD FOOTINGS ON SOIL ON LEDGE: N/A
- ALLOWABLE LOAD FOR PILING: N/A
- ESTIMATED LENGTH: N/A
- STRUCTURAL STEEL AASHTO M270M270M GRADE: S45W
- REINFORCING STEEL GRADE: 420
- CONCRETE CLASS A (HPC-A) f'c: 30 MPa
- CONCRETE CLASS B (HPC-B) f'c: 25 MPa
- SOIL UNIT WEIGHT: 22.00 Kn/m³
- DESIGN LOAD FOR SPREAD FOOTINGS ON SOIL: N/A

TRAFFIC MAINTENANCE

- IS TRAFFIC TO BE MAINTAINED?
IF YES, ON EXISTING STRUCTURE?
OR ON TEMPORARY BRIDGE?
ONE OR TWO-WAY TRAVEL? YES
YES; (COMBINATION ON BRIDGE & DETOUR)
N/A
N/A
- TRAFFIC CONTROL SIGNALS REQUIRED? NO
- ARE SIDEWALKS REQUIRED?
IF SO, ON WHAT SIDE? YES, ON DOWNSTREAM SIDE OF EXISTING
BRIDGE DURING PHASE ONE, UPSTREAM SIDE
OF NEW BRIDGE DURING PHASE TWO.

PROJECT NAME: **BRATTLEBORO**

PROJECT NUMBER: **BHF 2000 (17)**

FILE NAME: 194j078\Structures\j078p1.xls PLOT DATE: 01/28/2003

PROJECT MANAGER: R. R. WHITCOMB DRAWN BY: G. ROY

DESIGNED BY: T. SUMNER CHECKED BY: T. SUMNER

PRELIMINARY INFORMATION SHEET SHEET 2 OF 71