

STATE OF VERMONT
AGENCY OF TRANSPORTATION

ITEM DETAIL SUMMARY SHEET 3

BEGIN STATION	END STATION	POS.	203.30 EARTH BORROW	204.20 TRENCH EXCAV. OF EARTH	204.22 TRENCH EXCAV. OF EARTH, EXP. (N.A.B.I.)	204.30 GRAN. BACKFILL FOR STRUCTURES	402.12 AGG. SHOULD.	601.0010 15" CSP .064 (2-2/3 X 1/2)	601.0015 18" CSP .064 (2-2/3 X 1/2)	601.0815 18" RCP CLASS III	601.2615 18" CPEP (SL)	604.412 REHAB. D. I. CLASS I	613.10 STONE FILL. TYPE I	613.11 STONE FILL. TYPE II	619.17 YIELDING MARKER POSTS	621.205 STEEL BEAM G.R., GALV W/8 FT POSTS	621.207 STEEL BEAM G.R., GALV/NEST W/8 FT POSTS	621.215 HD STEEL BEAM G.R., GALV W/8 FT POSTS	621.60 ANCHOR FOR S.B. G.R.	621.80 REMOVE & DISP. OF G.R.	649.31 GEOT. UNDER STONE FILL	653.20 TEMP. EROS. MATT.	651.35 TOP-SOIL	676.10 DEL.INE. WITH STEEL POSTS	676.12 REMOVAL OF EXIST. DEL.INE.	REMARKS	
			CY	CY	CY	CY	TON	LF	LF	LF	LF	EACH	CY	CY	EACH	LF	LF	LF	EACH	LF	SY	SY	CY	EACH	EACH		
NEW HAVEN																											
b 80+50	b 86+25	LT											92.5	10							277.5	277.5					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 83+55.75	b 85+80.75	RT	50													191.5	37.5		2			50	10	2			INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA. b 83+55.75 AND STA. b 85+80.75
B 83+46	B 85+71															204	25										
b 84+75	b 85+40	RT											23.7	10							71.1	71.1					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 84+49.25	b 86+74.25	LT	50													191.5	37.5		2			50	10	2			INSTALL 12' -6" LONG, 16' RADIUS WITH ANCHOR AT STA. b 84+49.25 AND STA. b 86+74.25
B 84+40	B 86+69															204	25										
b 91+75	b 92+25	RT											9.2								27.6	27.6					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 93+75	b 95+70	LT											35.3								105.9	105.9					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 93+75	b 94+25	RT											10.8								32.4	32.4					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 94+19.75	b 96+44.75	RT	50											10		191.5	37.5		2			50	10	2			INSTALL 12' -6" LONG, RADIUS WITH ANCHOR AT STA. b 94+19.75 AND STA. b 96+44.75
B 92+37	B 96+49.5															391.5	25										
b 95+17.25	b 97+42.25	LT	50											10		191.5	37.5		2			50	10	2			INSTALL 12' -6" LONG, RADIUS WITH ANCHOR AT STA. b 95+17.25 AND STA. b 97+42.25
B 95+08.5	B 101+46															616.5	25										
b 97+25	b 100+25	LT											63.2								189.6	189.6					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 99+00	b 100+48	RT											27.7								83.1	83.1					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
b 111+75	b 114+25	LT											39.5								118.5	118.5					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
WALTHAM																											
c 0+00	c 48+77.02	LT&RT					220								14												ESTIMATED QUANTITIES TO BE USED AS DIRECTED BY THE RESIDENT ENGINEER
c 2+30	c 2+45	RT											1.9								5.7	5.7					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
c 5+25	c 8+25	LT											58.3								174.9	174.9					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
c 6+77.86	c 6+93.75	LT&RT		1		1				6																	EXTEND EXISTING 18" RCP CULVERT 3' AT INLET AND OUTLET
c 9+45	c 16+70	LT														759			2	725		50	10	2	2		INSTALL 12' -6" LONG, RADIUS WITH ANCHOR AT STA. c 9+45 AND STA. c 16+70
C 9+50																741.5											
c 12+93.40	c 12+94.90	RT		1		1			3																		EXTEND EXISTING 18" CSP CULVERT
c 25+75	c 27+00	LT											38.1								114.3	114.3					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
c 29+25	c 36+75	LT											170.2								510.6	510.6					PLACE STONE FILL ON SLOPES GREATER THAN 1:2 FOR SLOPE STABILIZATON
TOTAL			200	2	-	2	220	-	3	6	-	-	570.4	40	14	1525	150	-	10	725	1711.2	1961.2	50	10	2		

ITEM
DETAIL
SUMMARY
SHEET 3

PROJECT NAME: ADDISON - NEW HAVEN
PROJECT NUMBER: STP 9632(1)
FILE NAME: p95B076.dgn PLOT DATE: 3/13/2012
PROJECT LEADER: CDL DRAWN BY: SJL
DESIGNED BY: SJL CHECKED BY: EPD
PLOT FILE: p95B076.17.1 SHEET 17 OF 186