



SURFACE/OVERLAY COURSE:	1-1/2" TYPE III (PLACED IN ONE LIFT)
BINDER COURSE :	3" TYPE II (PLACED IN ONE LIFT)
BASE COURSE:	4" TYPE I (PLACED IN ONE LIFT)
SUBBASE MATERIAL:	24" DENSE GRADED CRUSHED STONE (704.06)

- NOTES:
- CONTRACTOR SHALL MATCH EXISTING PAVEMENT THICKNESS IF GREATER THAN 8-1/2" AND AS DIRECTED BY THE ENGINEER, BY INCREASING TOTAL THICKNESS OF BASE COURSE PLACED IN TWO LIFTS INSTEAD OF ONE.
  - PERFORMANCE GRADED BINDER USED FOR THE BITUMINOUS CONCRETE PAVEMENT SHALL BE A PG 70-28

**PAVEMENT SCHEDULE**  
NTS

**CONTRACT PLANS**

**VERMONT AGENCY OF  
TRANSPORTATION**

**WILLISTON NHG 5500 (10)S  
"TAFT CORNERS"  
(US ROUTE 2 & VT ROUTE 2A)**

WILLISTON	VERMONT
<b>TYPICAL SECTIONS</b>	desi gn RJD
	drawn JLC
	checked RJD
<b>LAMOUREUX &amp; DICKINSON</b> <b>Consulting Engineers Inc.</b> 14 Morse Drive Essex Junction, VT 05452 (802) 878-4450 <b>Engineers-Planners-Surveyors</b>	scale NTS
	sht. no. <b>6</b>