

| STATION | | POS. | 203.15 | 203.16 | 203.30 | 212.20 | 212.20 | 301.28 | 402.12 | | 604.40 | 604.412 | 604.42 | 604.47 | 616.28 | 616.40 | 616.41 | 616.47 | 618.10 | 618.15 | 629.20 | REMARKS |
|--------------------|----------|-------|------------------------------|----------------------------------|-----------------------------|--|--|----------------------------|------------------|---------------|--------------|---------------------|----------------------------|-----------------------------------|--|-------------------------------|----------------------------|--|--|--------------------------|-----------------------------|--|
| BEGIN | END | | COMMON EXCAV. m ³ | SOLID ROCK EXCAV. m ³ | EARTH BORROW m ³ | SCARIFYING PAVEMENT (MOD.1) m ² | SCARIFYING PAVEMENT (MOD.2) m ² | SUBBASE OF C.R. GRAVEL (T) | AGG. SHOULDERS T | GRATE TYPE EA | CHAN ELEV EA | REHAB DI CLASS I EA | CHAN ELEV SEWER MANHOLE EA | CAST IRON GRATE W/FRAME TYPE D EA | CAST-IN-PLACE CEM. CONC. CURB TYPE B M | REMOVING & RESETTING CURB (M) | REMOVAL OF EXISTING CURB M | BIT. CONC. GUTTERS & TRAFFIC ISLANDS T | P.C. CONCRETE SIDEWALK 125 mm m ² | BIT. CONCRETE SIDEWALK T | ADJUST ELEV OF VALVE BOX EA | |
| VT ROUTE 36 | | | | | | | | | | | | | | | | | | | | | | |
| I+406.0 | 2+397.92 | LT&RT | | | | | | | | | 30 | | 9 | | | | | | | | 15 | QUANTITIES FOR USE AS DIRECTED BY THE ENGINEER. FOR STRUCTURE LOCATIONS, SEE SHEET 89. |
| I+406.0 | | RT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+409.0 | | LT | 0.5 | | | | 2.3 | 0.9 | | | | | | | | | | | | 0.3 | | CONSTRUCT BITUMINOUS SIDEWALK RAMP, TYPE I; FOR TEXTURING DETAILS, SEE SHEET 7. |
| I+413.0 | | RT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+417.0 | | LT | 1.4 | | | | 2.3 | 2.4 | | | | | | 3.9 | 3.9 | | | | | 0.8 | | CONSTRUCT BITUMINOUS SIDEWALK RAMP, TYPE I; FOR TEXTURING DETAILS, SEE SHEET 7. |
| I+498.9 | | LT | 1.5 | 0.5 | | | | 3.5 | | | | | | 7.9 | 7.9 | | | 10.1 | | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| I+498.9 | | RT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+511.3 | | RT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+511.3 | | LT | 1.0 | 0.9 | | | | 2.4 | | | | | | | | | | | 6.9 | | | CONSTRUCT SIDEWALK RAMP, TYPE 6 |
| I+591.2 | | RT | 0.3 | 0.3 | | | | 0.7 | | | | | | 3.4 | 3.4 | | | | 2.1 | | | CONSTRUCT SIDEWALK RAMP, TYPE 2 |
| I+594.0 | | LT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+651.8 | | LT | 0.5 | 0.4 | | | | 1.2 | | | | | | | | | | | 3.4 | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| I+655.0 | | RT | 0.5 | 0.3 | | | | 1.1 | | | | | | 2.3 | 2.3 | | | | 3.3 | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| I+661.0 | | LT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+666.0 | | RT | 1.4 | 0.9 | | | | 3.1 | | | | | | | | | | | 9.0 | | | CONSTRUCT SIDEWALK RAMP, TYPE 6 |
| I+782.0 | | LT | | | | 1.4 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| I+788.0 | | LT | 0.6 | 0.5 | | | | 1.3 | | | | | | 4.6 | 4.6 | | | | 3.7 | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| I+940.0 | | LT | 0.4 | 0.3 | | | | 0.8 | | | | | | | | | | | 2.4 | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| I+948.0 | | LT | 0.4 | 0.3 | | | | 1.0 | | | | | | | | | | | 2.8 | | | CONSTRUCT SIDEWALK RAMP, TYPE I |
| 2+038.0 | | RT | 0.4 | 0.3 | | | | 0.8 | | | | | | | | | | | 2.4 | | | CONSTRUCT SIDEWALK RAMP, TYPE 3 |
| 2+041.5 | | LT | 0.5 | 0.4 | | | | 1.2 | | | | | | | | | | | 3.4 | | | CONSTRUCT SIDEWALK RAMP, TYPE 2 |
| 2+048.0 | | RT | | | | 2.3 | | | | | | | | | | | | | | | | CONSTRUCT TEXTURING. FOR DETAILS SEE SHEET 7. |
| SEE REMARKS | | | | | | | | | | | | | | 3.0 | 3.0 | | | | | | | CURB ITEMS FOR USE IN CONJUNCTION WITH WIRED CONDUIT INSTALLATION AS DIRECTED BY THE RESIDENT ENGINEER. FOR DETAILS, SEE SHEET 10. |
| SUBTOTALS | | | 9.4 | 5.1 | | 17.5 | 4.6 | 20.4 | | | 30 | | 9 | 25.1 | 25.1 | | | | 49.5 | 1.1 | 15 | |
| ROUNDING | | | 0.6 | 0.9 | | 0.5 | 0.4 | 0.6 | | | - | | - | 0.9 | 0.9 | | | | 1.5 | 0.9 | - | |
| PROJECT TOTALS | | | 10 | 6 | | 18 | 5 | 21 | | | 30 | | 9 | 26 | 26 | | | | 51 | 2 | 15 | |

| | |
|---|--------------------------------------|
| PROJECT NAME : ST. ALBANS CITY | PROJECT NO. : STP 2129(I)S |
| DESIGN FILE NAME: /pave/99d070/pd070.dgn IPARM FILE NAME: pd0701d1 | PLOT DATE: 01-FEB-2006 0 |
| SURVEYED BY: D-H | SURVEY DATE: 09/98 |
| DESIGNED BY: JLL | DRAWN BY: D-H |
| | SHEET: 74 OF 105 |