

STATION		POS.	203.15	203.30	203.99	301.28	402.12	613.10	616.31	616.41	616.47	617.10	619.17	621.20	621.20	621.505	621.60	621.75	621.76	621.77	621.80	629.20	649.31	676.10	REMARKS		
BEGIN	END		COMMON EXCAV. m³	EARTH BORROW m³	SHLDR. BERM. REM. M	SUB. OF CR. GRAVEL T	AGGR. SHOUL. (MOD.) T	STONE FILL TYPE m³	BIT. CONC. CURB TYPE B T	REMOVAL OF EXIST. CURB M	BIT. CONC. GUTTERS T	RELOCATE MAIL BOX SING. SUPP. EA	YIELDING MARKER POSTS EA	STEEL BEAM G.R. M	STEEL BEAM G.R. W/2.4 POSTS (MOD.) M	MAN. TERMINAL SECTION (FLARED) EA	ANCHOR FOR STEEL BEAM RAIL EA	REMOVING AND RESET G.R. M	REPLACE G.R. POST ASSEMBLY EA	REPLACE G.R. BEAM UNIT EA	REMOVAL AND DISPOSAL OF G.R. M	ADJUST ELEVATION OF VALVE BOXES EA	GEOTEXTILE UNDER STONE FILL m²	DELINEATORS WITH STEEL POSTS EA			
<b>ST. ALBANS TOWN</b>																											
1+882.00	4+668.30	LT & RT				98.9	629						16									2				FOR VALVE BOX LOCATIONS, SEE SHEET 89. THE OTHER QUANTITIES LISTED ARE PROVIDED FOR USE AS DIRECTED BY THE RESIDENT ENGINEER.	
1+927.0	1+945.0	RT	4.8			9.6			0.9	2.4																CONSTRUCT ISLAND. FOR DETAILS, SEE SHEET 50.	
1+947.2	2+091.5	RT	7.9								18.8															FOR GUTTER DETAIL, SEE SHEET 50.	
2+640.0	2+803.0	RT	26.9								63.7															FOR GUTTER DETAIL, SEE SHEET 50.	
3+655.0	3+670.2	LT		40			10							15.2		2					11.4			1		INSTALL NEW STEEL BEAM GUARD RAIL WITH NEW ANCHORS AT STA. 3+658.1 & 3+666.5, LT.	
4+171.0	4+240.0	RT	3.8								9															FOR GUTTER DETAIL, SEE SHEET 50.	
4+535.0	4+633.8	LT		40			10							7.6		2					96.5			1		INSTALL NEW STEEL BEAM GUARD RAIL; INSTALL NEW MTS (FLARED) AT STA. 4+535.0 & 4+622.4, LT.	
4+554.3	4+630.3	RT		40			10							53.2		2					76.5			1		INSTALL NEW STEEL BEAM GUARD RAIL; INSTALL NEW MTS (FLARED) AT STA. 4+535.0 & 4+622.4, LT.	
<b>SWANTON</b>																											
0+000.0	8+155.20	LT & RT			95.1		2084						38					97	21	11						THE QUANTITIES LISTED ARE PROVIDED FOR USE AS DIRECTED BY THE RESIDENT ENGINEER.	
1+620.5	2+068.9	LT		40			10	3				2			425.6	2					445.1		15	1		INSTALL NEW STEEL BEAM GUARD RAIL W/ 2.4 M POSTS (MOD.); INSTALL NEW MTS (FLARED) AT STA. 1+620.5 & 2+057.5, LT; RELOCATE TWO MAILBOXES AT STA. 1+710.0 & 1+884.7, LT; STONE FILL, TYPE I FOR EROSION REPAIR - FOR DETAILS, SEE LAYOUT #69.	
7+764.6	7+776.0	LT		20			5									1					11.4			1		REPLACE EXISTING END TREATMENT WITH AN MTS (FLARED)	
7+796.2	7+800.0	RT		40			10							3.8		2					3.8					REPLACE EXISTING GUARD RAIL WITH NEW STEEL BEAM RAIL AND NEW ANCHOR AT STA. 7+796.2, RT.	
7+800.0	7+807.6	LT		40			10							7.6		2					7.6			1		INSTALL NEW STEEL BEAM GUARD RAIL WITH NEW ANCHORS AT STA. 7+803.8, LT. (2)	
FROM DITCHING								25															137			FOR LOCATIONS, SEE DITCH CLEANING DETAIL SHEET 52.	
<b>SUBTOTALS</b>																											
			43.4	260	95.1	108.5	2778	28	0.9	2.4	91.5	2	54	87.4	425.6	7	6	97	21	11	652.3	2	152	6			
<b>ROUNDING</b>																											
			1.6	-	1.9	2.5	52	1	0.1	0.6	2.5	-	-	2.6	4.4	-	-	-	-	-	7.7	-	3	-			
<b>TOTALS</b>																											
			45	260	97	111	2830	29	1	3	94	2	54	90	430	7	6	97	21	11	660	2	155	6			

PROJECT NAME: ST. ALBANS - SWANTON  
PROJECT NUMBER: STP 2335(I)S  
FILE NAME: /pave/01c016/p01c016.dgn PLOT DATE: 16-SEP-2005  
PROJECT LEADER: JLL DRAWN BY: D-H  
DESIGNED BY: D-H CHECKED BY: D-H  
IPARM FILE NAME: p01c016d1.i SHEET 56 OF 89