



TEMPORARY AND DURABLE 4" WHITE LINE
 STA 259+00 TO 266+50 SOLID RT AND LT
 (WITH EDGELINE BREAKS FOR TOWN HIGHWAYS)

TEMPORARY AND DURABLE 4" YELLOW LINE
 STA 259+00 TO 266+50 SOLID RT SOLID LT
 (WITH 40' BREAKS FOR CENTERLINE)

REHABILITATION OF DROP INLET, CATCH BASIN OR MANHOLE
 STA 259+28 LT STA 259+93 LT
 STA 259+53 LT STA 260+83 LT

REMOVING SIGNS
 AS SHOWN - 4

BITUMINOUS CONCRETE GUTTERS AND TRAFFIC ISLANDS
 STA 259+53 LT (ALONG EDGE OF TH 20)
 STA 259+93 LT (ALONG EDGE OF TH 20)
 STA 260+23 LT (ALONG EDGE OF TH 20)

ERECTING SALVAGED SIGNS
 AS SHOWN - 1

DITCHING LOCATIONS (REFER TO SHEET 7 FOR DETAILS)
 STA 260+83 TO 262+28 LT
 STA 262+49 TO 264+20 LT
 STA 265+38 TO 266+30 LT

INSTALLED NEW 12" x 30' CSP
 DRIVE CULVERT

MORGAN VT. ROUTE 111 PAVEMENT CORE INFORMATION

| CORE # | STATION/POS. | DEPTH (in) | STRIPPED | DRAINABLE BASE |
|--------|--------------|------------|----------|----------------|
| 19 | 266+48 RT | 5 | NO | NO |

PROJECT LAYOUT SHEET #29

DESIGNED BY LFW DATE 6/04
 DRAWN BY LFW DATE 6/04
 DESIGN FILE NO. pave/99cl92/99cl92.dgn
 PRF FILE 99cl92p29.I DATE PLOTTED 12-MAR-2007 11:33
 PROJ. NAME MORGAN
 PROJ. NO. AC STP 2220(1)S
 SHEET 36 OF 61 SHEETS