



**MORGAN CTR**  
**MORGAN 2**

REMOVING SIGNS  
AS SHOWN - 1

TEMPORARY AND DURABLE 4" WHITE LINE  
STA 266+50 TO 275+00 SOLID RT AND LT

TEMPORARY AND DURABLE 4" YELLOW LINE  
STA 266+50 TO 275+00 SOLID RT SOLID LT

DITCHING LOCATIONS (REFER TO SHEET 7 FOR DETAILS)  
STA 266+71 TO 268+37 LT  
STA 269+10 TO 273+02 LT  
STA 273+38 TO 275+00 LT

CURVE # 25  
△ 21° RT  
R=1620'  
D=3° 30'  
T=300'  
L=594'  
BANKING 0.058 FT/FT  
150' RUNOFF (50 MPH)  
SEE SHEET 52 FOR BANKING DETAIL

274+24 LT REMOVE  
**REDUCED SPEED AHEAD**

INSTALLED NEW  
12" x 36' CSP  
DRIVE CULVERT

MORGAN VT. ROUTE 111 PAVEMENT CORE INFORMATION				
CORE #	STATION/POS.	DEPTH (in)	STRIPPED	DRAINABLE BASE
20	274+56 LT	5 1/2	NO	NO

<p>PROJECT LAYOUT SHEET #30</p>	DESIGNED BY	LFW	DATE	6/04
	DRAWN BY	LFW	DATE	6/04
	DESIGN FILE NO.	pave/99cl92/99cl92.dgn		
	PRF FILE	99cl92p30.1	DATE PLOTTED	12-MAR-2007 11:3
	PROJ. NAME	MORGAN		
PROJ. NO.	AC STP 2220(1)S			
SHEET	37	OF	61	SHEETS