



KEY FOR ROOF REPAIRS:

- (R01) REPLACE DAMAGED ROOF SHEATHING TO MATCH EXISTING.
- (R02) SEE DETAIL 100, SHEET 42, TO FASTEN RAFTERS TO RIDGE BEAM.
- (R03) REUSE EXISTING MORTISE FOR NEW RAFTER. SEE DETAIL 101, SHEET 42
- (R04) SEE DETAIL 102, SHEET 42, TO REPAIR FAILED RAFTER SEAT AT TIE BEAM
- (R05) SEE DETAIL 103, SHEET 42 TO FASTEN RAFTERS TO TIE BEAM
- (R06) SEE DETAIL 104, SHEET 42, TO FASTEN RAFTERS TO TRUSS TOP CHORD

ROOF NOTES:

1. REPLACEMENT SHEATHING BOARDS SHALL GENERALLY BE CONTINUOUS OVER THREE SPANS MINIMUM WITH STAGGERED JOINTS LOCATED OVER SUPPORTS. SINGLE-SPAN REPLACEMENT PATCHES MAY BE USED WHERE INDICATED IN THE ROOF PLAN.
2. ALL EXISTING AND REPLACEMENT ROOF SHEATHING SHALL BE FASTENED WITH A MINIMUM OF (3) SOUND 8D COMMON NAILS AT EACH SUPPORT. SEE NOTES 1 AND 2 FOR "FASTENERS FOR LUMBER AND TIMBER" ON SHEET 24 FOR PAYMENT OF ADDED FASTENERS.

LEGEND

- PREDETERMINED MEMBERS TO BE REPLACED (SIZE TO MATCH EXISTING, UNLESS OTHERWISE NOTED)
- PREDETERMINED PORTION OF EXISTING MEMBER TO BE REPLACED (MATCH SIZE OF EXISTING)
- ADDED MEMBER
- EXISTING MEMBER TO BE REMOVED
- ROOF REPAIR KEY NUMBER

PROJECT NAME:	CHARLOTTE	FILE NAME:	z06j088details_truss.dgn	PLOT DATE:	9/14/2012
PROJECT NUMBER:	BHO 1445(34)	PROJECT LEADER:	M.A. COLGAN	DRAWN BY:	K.D. WENTWORTH
		DESIGNED BY:	K.E. HILL	CHECKED BY:	M.A. COLGAN
		ROOF PLAN		SHEET	26 OF 55

