

All SMH's

- NO EXCEPTION TAKEN
- MAKE CORRECTIONS NOTED
- REJECTED
- REVISE AND RESUBMIT
- SUBMIT SPECIFIED ITEM

Bay Oil Company
 38 Plainfield Street
 Chicopee, MA 01013

Telephone: (413) 737-7728
 FAX: (413) 737-7730

Ebony
 Waterproof and concrete sealer

CHECKING IS ONLY FOR THE GENERAL CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND GENERAL COMPLIANCE WITH THE INFORMATION GIVEN IN THE CONTRACT DOCUMENTS. ANY ACTION SHOWN IS SUBJECT TO THE REQUIREMENTS OF THE PLANS AND SPECIFICATIONS. CONTRACTOR IS RESPONSIBLE FOR DIMENSIONS WHICH SHALL BE CONFIRMED AND CORRELATED AT THE JOB SITE; FABRICATION PROCESSES AND TECHNIQUES OF CONSTRUCTION; COORDINATION OF WORK WITH THAT OF ALL OTHER TRADES AND THE SATISFACTORY PERFORMANCE OF THE WORK.



DATE 3/25/2015 BY James Rashford

DESCRIPTIONS

- EBONY is a general purpose waterproof and concrete sealer
- Water and polymer based
- Manufactured from environmentally friendly, low VOC components

FEATURES

- For use on all types of concrete structures
- Non-Toxic environmentally friendly
- Extremely low VOC - meets requirements ASTM D 3792
- Creates a smooth, hard polymer film that protects the structure from water intrusions and chemical attack
- Quick fast drying 5-10 min. @ 72 F allowing rapid transportation of parts
- Roll on, spray, brush, 300-350 sq.ft./gallon
- Quick clean up, just soap and water removes from parts and skin
- No dangerous solvents
- Fire safe, water based
- Superior to asphalt based sealers, fast drying and cleanup, better coverage
- Graco Sprayer, .011”-.013” tip (Graco 1-800-328-0211)

PRODUCT USES

- Designed as a waterproof on;
- Manholes
- Septic tanks
- Utility vaults
- Concrete pipe
- Burial vaults

PHYSICAL AND CHEMICAL PROPERTIES

VOC	96.25 grams/liter
Density @ 77 F	8.25-8.45 lb/gal
Percent Solids (ASTM D 1644.75)	By weight 35%
Viscosity	25 sec . Zahn #2 @ 77 F
PH	8.5
Dry Time	5-10 minutes @ 77 F
Film Thickness	1.5 mils per coat
Coverage	275-350 sq.ft./gal.