

**Exodermic Weight Calculation - Cast-in-place**

VT - Richmond Truss	
Panel length (direction main grid bars)	21.167 ft.
Panel width	8.000 ft.
No. of composite beams per panel	4
Concrete type	Normal weight
Concrete weight	145 lbs/cu.ft.
Concrete thickness	5 in.
Top rebar size	4
Top rebar spacing	4 in.
Bottom rebar size	4
Bottom rebar spacing	8 in.
"Haunch" height (see note)	4.445 in. (May vary.)
"Haunch" width	8.99 in.
Connection between panels - height	7.945 in.
Connection between panels - width	8 in.
Main bar weight	5 lbs/lin.ft.
Main bar spacing	12 in.
Distribution bar height	1.5 in.
Distribution bar thickness	0.25 in.
Distribution bar spacing	6 in.
Galv. horiz sheet metal (gauge)	20 gauge

<b>WEIGHTS</b>	
Main bars	5.0 lbs./s.f
Distribution bars	2.5 lbs./s.f
Galv. horiz sheet metal	1.4 lbs./s.f
Weight of Steel Grid	8.9 lbs/sf

Concrete	60.4 lbs/sf
Rebar	3.3 lbs/sf
less concrete displaced by steel	-1.6 lbs/sf

**WEIGHT OF EXODERMIC DECK 71.1 lbs/sf**

Plus additional concrete for full depth "haunch"	7.6 lbs/sf
less haunch concrete displaced by steel in haunch	-0.3 lbs/sf
Plus additional concrete for connection between panels	2.5 lbs/sf

TOTAL INSTALLED WEIGHT before overlay	80.9 lbs/sf
TOTAL INSTALLED WEIGHT with overlay if specified	105.9 lbs/sf

Note: The term "haunch" is used here to describe the areas of the deck over beams where the grid is filled full depth.

The information provided herein was prepared with reference to generally accepted engineering practices. It is the responsibility of the user of this information to independently verify such information and determine its applicability to any particular project or application. DS Brown assumes no liability for use of any information contained herein.