



- NOTES:**
1. TRANSVERSE TENDONS SHALL BE COVERED BY SEAMLESS POLYPROPYLENE SHEATH (WITH CORROSION INHIBITOR GREASE BETWEEN SHEATH AND STRAND) FOR THE LENGTH OF STRAND, EXCEPT AT ANCHORAGE LOCATIONS. EACH STRAND SHALL BE TENSIONED TO 47 KIPS.
 2. ANCHOR PLATES SHALL CONFORM TO AASHTO M 270M/M 270, GRADE 345 (GRADE 50) AND BE GALVANIZED IN ACCORDANCE WITH AASHTO M 111M/M III.
 3. ANCHOR PLATES FOR TRANSVERSE POST-TENSIONING ARE TO BE DESIGNED BY THE FABRICATOR FOR THE SPECIFIC POST-TENSIONING SYSTEM USED. DETAILS FOR THE ANCHOR PLATE SHALL BE PROVIDED ON THE FABRICATION DRAWINGS.

PROJECT NAME:	BARTON VILLAGE
PROJECT NUMBER:	BHF 0286(5)
FILE NAME:	z12j172supl.dgn
PROJECT LEADER:	J. OLUND
DESIGNED BY:	B. TOOTHAKER
FRAMING PLAN	
PLOT DATE:	7/26/2016
DRAWN BY:	S. MORGAN
CHECKED BY:	T. POULIN
SHEET	86 OF 110

TYLININTERNATIONAL