

# TYPICAL SECTIONS

TOLERANCES APPLY TO THICKNESS ONLY.

3" BITUMINOUS CONCRETE PAVEMENT ITEM 406.25 ± 1/4" (TO BE PLACED IN TWO COURSES, 1-1/4" TYPE III, OVER  
 24" SUB-BASE OF DENSE GRADED CRUSHED STONE ITEM 301.35 ± 1" (1-3/4" TYPE II)  
 0-24" SAND BORROW ITEM 203.31 ± 1" ] TO BE PLACED AS NOTED ON THE PLANS  
 0-12" GRANULAR BORROW ITEM 203.32 ± 1" ] OR AS DIRECTED BY THE ENGINEER

SHOULDERS 3" GRAVEL SURFACE COURSE, ITEM 401.10

## GENERAL NOTES

SEED, ITEM 651.10		TO BE APPLIED AS DIRECTED BY THE ENGINEER		
% WT	LBS/A	NAME	PUR %	GERM %
3.33	2	CROWN VETCH	97	75
50.00	30	CREeping RED FESCUE	98	85
8.33	5	TIMOTHY	99	85
16.67	10	PERENNIAL RYE GRASS (VAR. PENNFINE)	95	85
8.34	5	ALFALFA (VAR. SARANAC)	99	85
8.33	5	BIRDSFOOT TREFOIL (VAR. EMPIRE)	98	85
5.00	3	HIGHLAND BENT GRASS	92	65
100.00	60 LBS/ACRE			

THE SEED MIXTURE SHALL NOT HAVE A WEED CONTENT EXCEEDING 0.40% BY WEIGHT AND SHALL BE FREE OF ALL NOXIOUS WEED SEED.

MARKER POSTS, (WOOD)  
 TO BE PLACED AS DIRECTED BY THE ENGINEER

FERTILIZER, ITEM 651.15  
 FORMULA 10-20-10 TO BE USED WITH SEED,  
 ITEM 651.10 APPLIED AT THE RATE OF 500 LBS/ACRE.

AGRICULTURAL LIMESTONE, ITEM 651.20  
 TO BE APPLIED AT RATE OF 2 TONS/ACRE  
 OR AS DIRECTED BY THE ENGINEER.

HAY MULCH, ITEM 651.25  
 TO BE PLACED ON EARTH SLOPES AT THE RATE OF  
 2 TONS/ACRE

TOPSOIL, ITEM 653.10  
 TO BE USED WITH SEED, ITEM 651.10 IN RESIDENTIAL  
 AREAS, AS DIRECTED BY THE ENGINEER

SEE STANDARD SHEET B-5 FOR TYPICAL SLOPE ROUNDING  
 SEE STANDARD SHEET D-2 FOR PAY LIMITS OF SAND  
 BORROW WHEN USED IN CONJUNCTION WITH UNDERDRAIN

