


VERTICAL BLOCKING DIAGRAM FOR GIRDER LINES 1 THRU 5

LINE	(A)	(B)	(C)
1	4'-2 1/8	5 1/8	9 1/8
2	4'-2 1/8	6 1/8	9 1/8
3	4'-2 1/8	6 1/2	9 1/8
4	4'-2 1/8	6 3/8	9 1/8
5	4'-3 3/8	7 1/2	9 1/8

NOTES:

- FOR GENERAL NOTES, SEE SHT. GN1.
- ALL HOLES FOR SPLICES SHALL BE SUBPUNCHED OR SUBDRILLED $\frac{1}{8}''$ AND REAMED TO $\frac{3}{8}''$ WITH ALL PARTS ASSEMBLED OR DRILLED TO $\frac{1}{8}''$ FROM SOLID.
- ALL LONGITUDINAL DIMENSIONS IN THE VERTICAL BLOCKING DIAGRAM ARE DEVELOPED ALONG THE ROTATED REFERENCE LINE.
- ALL GIRDERS MUST BE ASSEMBLED AS PER THE DIAGRAM SHOWN PRIOR TO REAMING OR DRILLING. FOR FIELD SPLICE DETAILS, SEE DWG. 12-10.

RECEIVED
 CK'D BY *WES* OK'D BY _____
 AUG 27 2001
 RESUBMIT _____ APPROVED
 BY *CPW* DATE *8/30/01*

ITEM NO. 506.55	BR. NO. 3	PROJ. NO. BRZ 1444(22)
TITLE: BLOCKING DIAGRAMS FOR APPROVAL		
APPROVED:		
PRINT DIST.		
5	4-7-01	APPR.
ORIG.	FAB.	
5	7-13-01	APP
5	8-24-01	APP
 National Eastern Corporation Plainville, Connecticut		
JOB: T.H. 1 OVER THE WHITE RIVER ROYALTON, VERMONT		
CUSTOMER: BECK & BELLUCCI, INC.		
DESIGNER: VERMONT AGENCY OF TRANSPORTATION		
CHECKED	TS	3/01
DRAWN	AV	3/01
WORK ORDER NO.	DRAWING NO.	REV.
15873	70-1	A

OK