

Interthane® 990 HS
Polyurethane

ADDITIONAL INFORMATION Further information regarding industry standards, terms and abbreviations used in this data sheet can be found in the following sections of the International Protective Coatings data manual:

- Definitions & Abbreviations
- Surface Preparation
- Paint Application
- Theoretical & Practical Coverage

Individual copies of these information sections are available upon request.

SAFETY PRECAUTIONS This product is intended for use only by professional applicators in industrial situations in accordance with the advice given on this sheet, the Material Safety Data Sheet and the container(s), and should not be used without reference to the Material Safety Data Sheet (MSDS) which International Protective Coatings has provided to its customers. All work involving the application and use of this product should be performed in compliance with all relevant national, Health, Safety & Environmental standards and regulations.

In the event welding or flame cutting is performed on metal coated with this product, dust and fumes will be emitted which will require the use of appropriate personal protective equipment and adequate local exhaust ventilation.

If in doubt regarding the suitability of use of this product, consult International Protective Coatings for further advice.

Warning: Contains isocyanate. Wear air-fed hood for spray application.

PACK SIZE

5 gallon unit	Interthane 990 HS Base	4.5 gallons in a 5 gallon container
	Interthane 990 HS Curing Agent	0.5 gallons in a 1 gallon container
20 liter unit	Interthane 990 HS Base	18 liters in a 20 liter container
	Interthane 990 HS Curing Agent	2 liters in a 2.5 liter container

For availability of other pack sizes contact International Protective Coatings

SHIPPING WEIGHT U.N. Shipping No. 1263

5 gallon unit	61.2 lb (27.7 kg) Base (Part A) 4.5 lb (2.0 kg) Curing Agent (Part B)
20 liter unit	65.5 lb (29.7 kg) Base (Part A) 5.5 lb (2.5 kg) Curing Agent (Part B)

STORAGE Shelf Life 12 months minimum at 77°F (25°C). Subject to re-inspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.

Disclaimer

The information given in this sheet is not intended as a substitute for the professional advice of a qualified person. It is given as a guide only. It is the responsibility of the user to ensure that the product is used in accordance with the instructions on the container and the Material Safety Data Sheet. The user should consult the Material Safety Data Sheet for further information. The user should also consult the relevant national, Health, Safety & Environmental standards and regulations. The user should also consult the relevant national, Health, Safety & Environmental standards and regulations. The user should also consult the relevant national, Health, Safety & Environmental standards and regulations.

It is the user's responsibility to check this sheet is current prior to using the product. Issue date: 1st July 1997

© 1997 International Protective Coatings (Holding) Ltd. Copyright © International Protective Coatings Ltd. 1997.

International Protective Coatings

Head Office: London W1A 2PB England	Africa: Cape Town 8001 Singapore 04877	Asia: Cebu 6000 Hong Kong Singapore 04877	Europe: London W1A 2PB Tel: (44) 20 7491 1111 Fax: (44) 20 7491 1112	France: Paris 75001 Tel: (33) 1 47 00 11 11 Fax: (33) 1 47 00 11 12	Germany: Munich 80335 Tel: (49) 89 23 00 11 11 Fax: (49) 89 23 00 11 12	Italy: Milan 20121 Tel: (39) 02 76 00 11 11 Fax: (39) 02 76 00 11 12	Japan: Tokyo 100 Tel: (81) 3 55 61 11 11 Fax: (81) 3 55 61 11 12	North America: Houston, TX 77001 Tel: (1) 281 444 11 11 Fax: (1) 281 444 11 12	South America: Sao Paulo, SP Tel: (55) 11 508 11 11 Fax: (55) 11 508 11 12
--	---	---	--	---	---	--	--	--	--

USA Toll Free Number 800 588 1287
www.international-protective.com