



NOTES:

- EXISTING VERTICAL REINFORCING IN THE BEAM SEAT AND WINGWALLS TO BE RETAINED IF POSSIBLE. ANY RETAINED REINFORCING SHALL BE BLAST CLEANED PER SUPPLEMENTAL SPECIFICATION 580.
- AREAS OF CONCRETE SURFACE REPAIR ON EXISTING ABUTMENT TO BE DETERMINED IN THE FIELD BY THE ENGINEER AND PAID FOR UNDER ITEM 580J3 (MOD) AND ITEM 580J4 (MOD). SEE SHT. 28 FOR ADDITIONAL INFORMATION

NOTE:

VIF - VERIFY IN FIELD
NF - NEAR FACE
FF - FAR FACE
EF - EACH FACE
▲ - CUT TO FIT IN FIELD
3" CLR. FOR NEW REINFORCING UNLESS OTHERWISE SPECIFIED ON THE PLANS.



STATE OF VERMONT AGENCY OF TRANSPORTATION	
Town Of NORWICH	Bridge No. 46
Highway No. T.H. 3	Log Sta. Sur. Sta.
TOWN HIGHWAY NO. 3 OVER OMPOMPANOOSUC RIVER	
ABUTMENT #1 DETAILS	
Designed By S. BURBANK	Drawn By A. THIBAUT
Checked By M. CHENETTE	Bridge Design Supervisor
Date 12/03	Date 12/03
PROJECT NORWICH	PROJECT NO. TH2-9625
DH CAD Filename: ...Norw-abut1.dgn	Plot Date: 03/31/2004
Bridge Sheet No.	Sheet 26 of 40