



TBM: CHISELED SQUARE
IN CONCRETE PAD
ELEV. = 471.73

TBM: FLAT NAIL
IN UP #3/2X
ELEV. = 479.44

TYPE 1 STONE FILL WITH GEOTEXTILE
UNDER STONE FILL. EXCAVATION FOR
THIS AREA WILL BE PAID AS
ITEM 203.15, COMMON EXCAVATION

REMOVE EXISTING DOORS
& REPLACE WITH NEW
DOORS PER DETAILS ON
SHEET A-1

SALT SHED TO BE REMOVED BY
OTHERS (NOT IN CONTRACT)



LEGEND

- EUG — EXISTING UNDERGROUND UTILITIES
- PUG — PROPOSED UNDERGROUND UTILITIES
- ▨ CONSTRUCT PAVED DRIVE WITH 12" SUBBASE OF CRUSHED GRAVEL (FINE GRADED) AND PAVE WITH 3" BCP. EXCAVATION FOR THIS AREA SHALL BE PAID AS ITEM 203.15, COMMON EXCAVATION. SEE DETAIL H

EXISTING SURFACES REQUIRING EARTH BORROW SHALL BE SCARIFIED, PAID AS ITEM 212.20, SCARIFYING PAVEMENT, PRIOR TO PLACING BORROW.

PROJECT:	BENNINGTON SALT SHED	PROJECT NO.:	STP SALT(19)
DESIGN FILE NAME:	9825DDT.dgn	PLOT DATE:	04 MAR 1999
IPARM FILE NAME:	CLD CONSULTING ENGINEERS	SURVEY DATE:	10/98
SURVEYED BY:	J. WARNER	DRAWN BY:	P. HOLT
SQUAD LEADER:	J. WARNER	SHEETS:	SD-2

