



GENERAL NOTES:  
 1. ROOF DESIGN LOAD: LL=50 PSF  
 2. CAULK ALL JOINTS BETWEEN MASONRY AND DISSIMILAR MATERIALS  
 3. ALL EXTERIOR DOOR SHALL HAVE NON REMOVABLE PIN HINGES  
 4. PRECAST DOUBLE-TIE ROOF BEAMS ARE NOT TO BE PAINTED

INITIALS	DATE	REVISIONS
RM	6-5-78	
RM	6-12-78	

TYPE	SIZE	REMARKS
A	3'-0" x 7'-0" x 1 1/2"	28% see upper glazed light (wire gl.)
B	3'-0" x 6'-6" x 1 1/4"	20% upper glazed light (do.)
C	3'-0" x 6'-6" x 1 1/4"	21% upper glazed light (do.)
D	3'-0" x 6'-6" x 1 1/4"	dutch door with sheet 2 label
E	3'-0" x 7'-0" x 1 1/4"	bottom metal w/ pane bar 2 label
F	3'-0" x 6'-6" x 1 1/4"	2 label
G	3'-0" x 7'-0" x 1 1/4"	B label (BOILER ROOM)
H	4'-0" x 7'-0" x 1 1/4"	22% upper glazed light (wire gl.)

STATE OF VERMONT  
 DIVISION OF STATE BUILDINGS  
 AGENCY OF ADMINISTRATION  
 MONTPELIER, VERMONT  
 STANDARD HIGHWAY GARAGE BUILDING  
 WALL SECTIONS, MISC. DETAILS & DOOR SCHEDULE  
 DESIGNED BY: J.U.S.  
 DRAWN BY: S.H.MILLER  
 APPROVED BY: S.H.MILLER  
 DATE: AUG. 4, 75  
 DWG. NO. A-3  
 3 OF 5