



WALL SECTION - REAR ELEVATION  
THRU WINDOWS

WALL SECTION - FRONT ELEVATION  
THRU OVERHEAD DOOR AREA

TYPICAL SECTION AT O.H. DOOR  
PILAGER

**DOOR SCHEDULE**

TYPE	SIZE	REMARKS
A	3'-0" x 7'-0" x 1 1/2"	28" x 36" upper glazed light (wire gl.)
B	3'-0" x 6'-6" x 1 1/2"	26" x 33" upper glazed light (wire gl.)
C	3'-0" x 6'-6" x 1 1/4"	2" LABEL
D	3'-0" x 6'-6" x 1 1/2"	dutch door with shelf & lappet
E	3'-0" x 7'-0" x 1 1/2"	hollow metal w/ panic bar & lappet
F	3'-0" x 6'-6" x 1 1/4"	"B" LABEL
G	3'-0" x 7'-0" x 1 1/2"	"B" LABEL (BOILER ROOM)
H	4'-0" x 7'-0" x 1 1/4"	22" x 26" upper glazed light (wire gl.)
I	3'-0" x 7'-0" x 1 1/2"	22" x 26" upper glazed light (wire gl.)

NOTES:  
 1. DOORS & FRAMES TO BE FOLLOW METAL  
 2. ALL GLASS SHALL BE 1/4" POL. & GLASS (EXCEPT AS NOTED)  
 3. FOR FRAME DETAILS SEE SECTIONS ABOVE  
 4. EXTERIOR DOORS TO HAVE ALUMINUM SADDLES  
 5. DOORS TO BE WEATHER STRIPPED - ALL SIDES  
 6. SLOPE 6/16 x 1 3/4" SIMULATED TO DOOR B

**GENERAL NOTES:**

1. ROOF DESIGN LOAD: LL = 50# SQ FT
2. CAULK ALL JOINTS BETWEEN MASONRY AND DISSIMILAR MATERIALS.
3. ALL EXTERIOR DOORS SHALL HAVE NON-REMOVABLE PIN HINGES
4. PRECAST DOUBLE-TEE ROOF BEAMS ARE NOT TO BE PAINTED

**INITIALS** DATE REVISIONS

DATE: AUG. 4, '75  
 DESIGNED BY: J.V.S.  
 DRAWN BY: S.H. MILLER  
 APPROVED BY: [Signature]

**WALL SECTIONS, MISC. DETAILS & DOOR SCHEDULE**

STATE OF VERMONT  
 DIVISION OF STATE BUILDINGS  
 AGENCY OF ADMINISTRATION

VERMONT  
 STANDARD  
 HIGHWAY GARAGE BUILDING

DWG. NO. A-3  
 R-3W  
 R-5M

3 OF 5