



- GENERAL NOTES**
1. CONCRETE - 3000 P.S.I. @ 28 DAYS. MAXIMUM SLUMP 4".
 2. ALL EXPOSED CONCRETE TO BE RUBBED AND CURVED.
 3. ALL EXPOSED SLAB & CONCRETE STEPS TO BE RUBBED AND CURVED. DURATION OF JOB UNTIL ACCEPTANCE.
 4. EXPOSED CURB CORNERS TO BE CHAMFERED.
 5. ALL SLAB JOINTS TO BE IN PLACE MIN (3) DAYS @ 70°F. RE-SHORE AFTER STRIPPING PLANKS.
 6. MASONRY FROM CONCRETE - REINFORCING STEEL TO BE LAPED 40 DIA. & ALL RE-STEEL TO BE PLACED ON SLAB HOUSTERS & HI-CHAIRS. LEGS TO BE LVC. FLASHING, GROUT TO BE LAYED ABOVE BOTTOM FACE STEEL.
 7. ALL REINFORCING STEEL TO BE PLACED ON SLAB HOUSTERS & HI-CHAIRS. LEGS TO BE LVC. FLASHING, GROUT TO BE LAYED ABOVE BOTTOM FACE STEEL.
 8. ALL RE-STEEL TO BE PLACED ON SLAB HOUSTERS & HI-CHAIRS. LEGS TO BE LVC. FLASHING, GROUT TO BE LAYED ABOVE BOTTOM FACE STEEL.
 9. ALL CONCRETE SLABS SHALL BE CONCRETE.
 10. ALL CONCRETE SHALL HAVE INTEGRAL AGGREGATE WATER-REPELLENT.

NO.	BY	DATE	REVISION
A	TOS	2/27/75	COMP. OF SLABS

STATE OF VERMONT
DIVISION OF STATE BUILDINGS
AGENCY OF ADMINISTRATION

MONTPELLIER, VERMONT

Standard Highway Garage Building
DETAILS OF MEZZANINE, BOILER
ROOM SLABS AND CONC. STAIRWAY

SCALE: AS NOTED

DATE:	DESIGNED BY:	DWG. NO.
10-18-74	K.S.S.	A4
DRAWN BY:	APPROVED BY:	
STUDIO SEVEN INC.	[Signature]	4 OF 4