



STANDARD GARAGE BUILDING FOR VERMONT DEPARTMENT OF HIGHWAYS STATE BUILDINGS DIVISION DEPT. OF ADMINISTRATION VERMONT

NOTE: EQUIPMENT WALLS ARE SAME THICKNESS AS WALLS SHOWN ABOVE.

6" A.C. CLASS 1500

6" SUMP @ OUTLET

CONC. 3" x 3" x 1/2" L.T. BEYOND AT ENDS. AND OVER 2" O.C.

VARIES 8" MIN. AT HIGH POINT. PITCH TRENCH BOTTOM 1/4" PER FOOT.

NOTE: ALL DOORS AND POOR FRAMES TO BE HOLLOW METAL. ALL GLASS TO BE 1/2" POLI. IF GLASS. FOR FRAME DETAILS SEE ELSEWHERE ON THIS SHEET.

NOTE: 12" WALL IS SHOWN - OTHER WALLS ARE SHOWN.

FOOTING WIDTHS
 CHANGE TO ALLOW FOR REBAR AS FOLLOWS:
 Ipswich 1/2" - 27/31"
 WESTFIELD 1/2" - 27/31"

60 TO 70 OF 509PL
 #2 OIL BURNING TANK
 H.W.

1' Rise in Rk Above this level
 with
 look in level

NOTE AS TO LENGTH OF BUILDING

THE FLOOR PLAN ON THIS SHEET CONTAINS GENERAL INFORMATION ONLY WITH RESPECT TO THE LENGTH OF THE BUILDING. TWO TYPE 2 BAYS ARE ILLUSTRATED.

THE SUBJECT BUILDING FOR THIS PROJECT SHALL CONTAIN ONE TYPE 1 BAY ONE TYPE 3 BAY AND ONE TYPE 4 BAY. ALL AS SHOWN. HOWEVER THE SUBJECT BUILDING MAY CONTAIN FROM NONE TO THREE TYPE 2 BAYS. FOR SPECIFIC INFORMATION AS TO THE NUMBER OF TYPE 2 BAYS REQUIRED FOR THE SUBJECT BUILDING, SEE SHEET 1.

ALL TYPE 2 BAYS SHALL BE CONTIGUOUS, POSITIONED BETWEEN THE TYPE 1 BAY AND THE TYPE 3 BAY.

DIMENSION A (overall length) for BUILDING WIDTHS 0-TYPE 2 BAYS 15'-5 1/2"
 16'-0"
 16'-8"
 16'-4"
 16'-0"
 16'-0"

TYPE	SIZE	DOOR SCHEDULE
A	3'-0" x 7'-0" x 1/2"	26 x 30 UPPER GLAZED LIGHT
B	3'-0" x 6'-0" x 1/2"	26 x 30 UPPER GLAZED LIGHT
C	3'-0" x 6'-0" x 1/2"	17 x 25 BOTTOM LOUVER
D	3'-0" x 6'-0" x 1/2"	DUTCH DOOR WITH SHIELD
E	2'-4" x 6'-0" x 1/2"	
F	3'-0" x 6'-0" x 1/2"	