



GENERAL NOTES:

1. ROOF DESIGN LOAD: LL = 50* SQ. FT.
2. CAULK ALL JOINTS BETWEEN MASONRY AND DISSIMILAR MATERIALS.
3. ALL EXTERIOR DOORS SHALL HAVE NON REMOVABLE PIN HINGES.
4. PRECAST DOUBLE-TEE ROOF BEAMS ARE NOT TO BE PAINTED.

DOOR SCHEDULE

TYPE	SIZE	REMARKS
A	3'-0" x 7'-0" x 1 3/4"	26" x 36" upper glazed light (wire gl.)
B	3'-0" x 6'-6" x 1 3/4"	26" x 33" upper glazed light (do.)
C	3'-0" x 6'-6" x 1 3/4"	2" LABEL
D	3'-0" x 6'-6" x 1 3/4"	dutch door with shaft 2" LABEL
E	3'-0" x 7'-0" x 1 3/4"	hollow metal w/ pane bar 2" LABEL
F	3'-0" x 6'-6" x 1 3/4"	"B" LABEL
G	3'-0" x 7'-0" x 1 3/4"	"B" label (BOILER ROOM)

NOTES:

1. DOORS & FRAMES TO BE HOLLOW METAL.
2. ALL GLASS SHALL BE 1/4" POL. & GLASS (EXCEPT AS NOTED).
3. FOR FRAME DETAILS SEE SECTIONS ABOVE.
4. EXTERIOR DOORS TO HAVE ALUMINUM SADDLES.
5. DOORS TO BE WEATHERSTRIPPED - ALL SIDES.

STATE OF VERMONT
DIVISION OF STATE BUILDINGS
 AGENCY OF ADMINISTRATION
 VERMONT

STANDARD
 3 BAY HIGHWAY GARAGE BUILDING

WALL SECTIONS, MISC. DETAILS & DOOR SCHEDULE

DESIGNED BY: J. S. MILLER
 DRAWN BY: S. H. MILLER
 DATE: AUG. 4, '75
 APPROVED BY: [Signature]

INITIALS: [Blank]
 DATE: 6-5-76
 REVISIONS: [Blank]

DWG. NO. A-3
 3 OF 5