

SIGN	A	B	C	D	E	F	G
STD.	36	36	1/8	2 1/4	1 1/2	1 1/2	2 1/4
FW.	48	3 1/4	1 1/4	3 3/4	1 1/2	1 1/2	3

REVISIONS AND CORRECTIONS

- OCT. 30, 1987 - DATE OF ORIGINAL ISSUE
- JAN. 23, 1989 - DELETE MOTORCYCLE SYMBOL SIGN AND SPEED SIGN, ADDED TWO SIGNS
- OCT. 21, 1992 - ADDED A SIGN, REVISED A SIGN DIMENSION & TYPE ERROR & REVISED TITLE BLOCK
- AUG. 08, 1995 - ADDED FLAGGER GRID

APPROVED FOR THIS PROJECT AND/OR DESIGN IMPLEMENTATION. FIMA FINAL APPROVAL PENDING.


APPROVED

Thomas J. Kelly
DIRECTOR OF ENGINEERING
Paul A. Reed
TRAFFIC AND SAFETY ENGINEER

CONSTRUCTION SIGN DETAILS

(ALL DIMENSIONS SHOWN IN INCHES)

OTHER STDS. E-100 REQUIRED:



STANDARD E-102

NOTES

SEE STANDARD SHEET E-100 FOR NOTES AND TEXT DETAILS. COLORS FOR SIGNS SHOWN ON THIS SHEET SHALL BE BLACK TEXT, BORDER AND SYMBOLS SHALL BE ON A REFLECTORIZED ORANGE BACKGROUND OF TYPE III B OR TYPE III REFLECTIVE SHEETING, UNLESS OTHERWISE NOTED. THE EXCEPTION IS THE PADDLE SIGN.

SIGN DETAILS INDICATE THE APPROPRIATE COLOR.

SIGNS USED ONLY FOR DAYTIME MAINTENANCE OPERATIONS DO NOT NEED TO BE REFLECTORIZED. HOWEVER, THESE SIGNS SHALL BE LABELED "DAYTIME USE ONLY" ON THE BACK OF THE SIGN PANEL WITH 3" SERIES C LETTERS.

SIGN PADDLE FOR FLAGPERSON

STAFF DETAIL

MATERIALS: THE SIGN MATERIALS SHALL BE 0.063" ALUMINUM WITH COLORS AS INDICATED ON DETAILS. THE STAFF SHALL BE 1/2" DIAMETER RIGID ALUMINUM CONDUIT/TUBING WITH A WALL THICKNESS OF 0.25" OR 1" TO 1 1/2" DIAMETER RIGID PVC CONDUIT/TUBING WITH 0.25" WALL THICKNESS.

MOUNTING: THE STAFF SHALL BE MOUNTED WITH EITHER TWO 1/2" DIAMETER ALUMINUM BOLTS OR TWO 1/2" DIAMETER ALUMINUM RIVETS.

/trf/std/stge102.dgn : stge102.1