



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 MATERIALS & RESEARCH SECTION
 SUBSURFACE INFORMATION

BORING LOG

NEW HAVEN
 HES 032-1(8)
 VT-17 TH-18, TH-19, TH-22

Boring No.: B-101B
 Page No.: 1 of 1
 Pin No.: 04B210
 Checked By: MLM

Boring Crew: GARROW, JUDKINS, DAIGNEAULT
 Date Started: 12/13/12 Date Finished: 12/13/12
 VTSPG NAD83: N 593070.41 ft E 1476835.81 ft
 Station: 201+92 Offset: -0.10
 Ground Elevation: 416.21 ft

Casing: H.S.A. Sampler: SS
 I.D.: 3.25 in 1.5 in
 Hammer Wt: N.A. 140 lb.
 Hammer Fall: N.A. 30 in.
 Hammer/Rod Type: Auto/AWJ
 Rig: CME 45C SKID CE = 1.33

Groundwater Observations		
Date	Depth (ft)	Notes

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
0.0		Asphalt Pavement, 0.0 ft - 0.35 ft					
5.0		Field Note:, No Recovery, Refusal	(R)				
5.8		Hole stopped @ 5.8 ft Possible Top of Bedrock					

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
 2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
 3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.