



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 MATERIALS & RESEARCH SECTION
 SUBSURFACE INFORMATION

BORING NUMBER: B-4 MW #1
 SHEET 1 of 1
 DATE STARTED: 9/09/05
 DATE COMPLETED: 9/12/05

PROJECT NAME: WOLCOTT
 SITE NAME: RT. 15
 STATION: 3+89.26
 OFFSET: 36.00
 VTSPG: N 754348.31 ft E 1633650.27 ft

PROJECT NUMBER: RT. 15 SLIDE
 SITE NUMBER: SLIDE AREA
 GROUND ELEVATION: 683.16 ft
 GROUNDWATER DEPTH: 4.2 ft 9/13/05
 PROJECT PIN NUMBER: 04X507

BORING CREW
 CREW CHIEF: TALLMAN
 DRILLER: TALLMAN
 LOGGER: PORTER

BORING RIG: LAG TRACK RIG
 BORING TYPE:
 SAMPLE TYPE:
 CHECKED BY: DLG

DEPTH (ft)	SYMBOL	CLASSIFICATION OF MATERIALS (Description)	WELL DIAGRAM	BLOWS PER FOOT	M.C. (%)	GRAVEL (%)	SAND (%)	FINES (%)
		Top of Well Elevation: 685.25 ft						
		Top of Well casing is 2.5 ft. above ground level. Solid casing with Bentonite around it., 0.0 ft - 5.0 ft						
5		Screen casing with sand packed around it., 5.0 ft - 25.0 ft						
10								
15								
20								
25		One foot of sand under casing., 25.0 ft - 26.0 ft						
		Hole stopped @ 26.0 ft						
		DRILLER'S NOTES: 1. Monitoring Well #1 was installed. 2. There is 20.0 ft. of screen casing in ground. 3. There is 5.0 ft. of solid casing in ground. 4. There is 2.5 ft. of solid casing above ground. 5. Water depth was reported from top of ground surface.						
30								
35								

LOG OF BORING WOLCOTT RT.15 SLIDE.GPJ VT AOT.GDT 12/14/06