



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

MILTON
IM 089-3(66)
I-89 NB&SB BR-81 NB&SB

Boring No.: B-102
Page No.: 1 of 1
Pin No.: 10A060
Checked By: TDE

Boring Crew: PORTER, HOLT
Date Started: 8/11/11 Date Finished: 8/17/11
VTSPG NAD83: N 779305.00 ft E 1473652.53 ft
Station: 2781+31.7 Offset: 47.70
Ground Elevation: 208.0 ft

Casing Sampler
Type: WB SS
I.D.: 4 in 1.5 in
Hammer Wt: N.A. 140 lb.
Hammer Fall: N.A. 30 in.
Hammer/Rod Type: Auto/AWJ
Rig: CME 45C SKID CE = 1.33

Groundwater Observations

Date	Depth (ft)	Notes
08/17/11	49.0	AM

Depth (ft)	Strata (i)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
		Asphalt Pavement, 0.0 ft - 1.0 ft					
	X X X	Field Note:., 1.0'-2.6', Crushed Stone					
	O O O	A-2-4, Sa, brn, Moist, Rec. = 0.9 ft	2-5-5-7 (10)	11.5	1.2	85.5	13.3
10	O O O	A-1-a, SaGr, brn, Moist, Rec. = 0.5 ft, Broken Rock was within sample.	6-8-8-4 (16)	7.3	56.7	36.9	6.4
	O O O	A-3, Sa, brn, Moist, Rec. = 1.3 ft	8-21-31- 41 (52)	14.1	2.8	88.1	9.1
20	O O O	A-2-4, SiSa, brn, Moist, Rec. = 1.4 ft	9-11-13- 15 (24)	14.8	5.3	64.5	30.2
	O O O	A-2-4, Sa, brn, Moist, Rec. = 1.4 ft	15-26- 29-34 (55)	11.8	1.2	79.6	19.2
30	O O O	A-2-4, SiSa, brn, Moist, Rec. = 1.5 ft	12-19- 22-24 (41)	13.0	1.2	78.5	20.3
	O O O	A-3, Sa, brn, Moist, Rec. = 1.6 ft	20-32- 43-47 (75)	12.1	1.4	88.6	10.0
40	O O O	A-3, Sa, brn, Moist, Rec. = 1.5 ft	23-30- 36-43 (66)	14.0	5.9	84.1	10.0
	O O O	A-3, Sa, brn, Moist, Rec. = 1.65 ft	11-16- 20-25 (36)	13.5	5.5	87.2	7.3
50	O O O	A-3, Sa, brn, Moist, Rec. = 1.7 ft	12-14- 19-27 (33)	11.2	2.8	89.1	8.1
	O O O	A-3, Sa, brn, Moist, Rec. = 1.4 ft	8-14-21- 23 (35)	15.6	2.4	89.0	8.6
60	O O O	A-3, Sa, brn, Moist, Rec. = 1.3 ft	16-23- 21-21 (44)	17.9	1.8	88.9	9.3
		Field Note:., Rollar coned ahead to 72.0 feet., Unable to continue boring because of scheduled construction.					
		Hole stopped @ 72.0 ft NLTD					

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

BORING LOG 2 MILTON IM 089-3(66).GPJ VERMONT AOT.GDT 9/22/11