



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

EAST MONTPELIER
STP SCRIP(9)
VT. 14

Boring No.: B-202
Page No.: 1 of 1
Pin No.: 10B200
Checked By: CEE

Boring Crew: WERNER, WELLS
Date Started: 5/24/11 Date Finished: 5/24/11
VTSPG NAD83: N 637084.10 ft E 1643913.80 ft
Station: _____ Offset: _____
Ground Elevation: _____

Casing Type: H.S.A. I.D.: 3.25 in
Sampler Type: SS I.D.: 1.5 in
Hammer Wt: N.A. Hammer Fall: N.A.
Hammer/Rod Type: Auto/AWJ
Rig: CME 45C TRACK CE = 1.34

Groundwater Observations		
Date	Depth (ft)	Notes
05/24/11	9.0	

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %	LL %	PI %
		Field Note:, Asphalt Pavement							
		Field Class:, Gravel material							
5		A-4, SiSa, brn, Moist, Rec. = 1.3 ft	WH-4-4-4 (8)	12.6	18.5	41.3	40.2		
10		A-4, SaSi, gry, MTW, Rec. = 1.6 ft	1-3-2-4 (5)	22.7	3.3	34.4	62.3		
15		A-4, SaSi, gry, MTW, Rec. = 1.1 ft	1-1-2-2 (3)	22.7	6.6	27.2	66.2		
20		A-4, SaSi, gry, MTW, Rec. = 1.5 ft	1-2-3-3 (5)	25.2	5.0	36.5	58.5		
25		A-4, ClSi, gry, MTW, Rec. = 1.1 ft	3-5-6-11 (11)	17.1	3.1	20.7	76.2	27	8
		A-4, SaSi, gry, MTW, Rec. = 1.7 ft	3-10-13-17 (23)	14.0	15.1	25.1	59.8	20	2
		A-4, SaSi, gry, MTW, Rec. = 1.8 ft	7-10-21-18 (31)	10.2	9.6	34.4	56.0	18	2
30		A-4, ClSi, gry, MTW, Rec. = 1.5 ft	3-4-9-WH (13)	13.8	11.8	22.4	65.8	27	8
		A-7-6, SiCl, gry, MTW, Rec. = 2.0 ft	5-13-18-23 (31)	26.6		2.6	97.4	43	17
35		A-7-6, Cl, gry, MTW, Rec. = 1.6 ft	5-7-11-7 (18)	28.1		7.8	92.2	47	21
		A-7-6, SiCl, gry, MTW, Rec. = 1.7 ft	10-16-17-19 (33)	29.3		5.7	94.3	41	16
40		A-6, SiCl, gry, MTW, Rec. = 2.0 ft	9-13-12-14 (25)	29.3		7.4	92.6	33	11
		Hole stopped @ 40.0 ft NLTD							

BORING LOG 2 - EAST MONTPELIER STP SCRIP(9).GPJ VERMONT AOT.GDT 7/7/11

Notes:

1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.