



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 CONSTRUCTION AND
 MATERIALS BUREAU
 CENTRAL LABORATORY

BORING LOG

LYNDON
 STP 0113(65)
 US-5 MAST ARMS

Boring No.: B-101
 Page No.: 1 of 1
 Pin No.: 10C176
 Checked By: MRG

Boring Crew: NIETO, GARROW, GARDNER
 Date Started: 8/11/15 Date Finished: 8/11/15
 VTSPG NAD83: N 736461.89 ft E 1770263.17 ft
 Station: 94+08 Offset: 31.00
 Ground Elevation: 704.65 ft

Type: _____
 I.D.: _____
 Hammer Wt: _____
 Hammer Fall: _____
 Hammer/Rod Type: _____
 Rig: _____

Casing WB Sampler SS
4 in 1.5 in
N.A. 140 lb.
N.A. 30 in.
Auto/AWJ
CME 45C SKID C_r = 1.33

Groundwater Observations

Date	Depth (ft)	Notes
08/11/15	15.3	During Drilling.

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Groundwater Observations				
			Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
5		A-2-4, GrSa, brn, Moist, Rec. = 0.6 ft	2-3-7-7 (10)	3.5	27.0	58.1	14.9
		A-2-4, GrSiSa, brn, Moist, Rec. = 0.5 ft, Lab Note: Broken Rock was within sample. Small Glass fragments were noticeable.	6-6-6-4 (12)	8.4	23.1	47.9	29.0
		A-2-4, SiSa, brn, Moist, Rec. = 0.4 ft	5-4-5-5 (9)	8.7	2.0	72.4	25.6
		A-2-4, SiSa, brn, Moist, Rec. = 0.9 ft, Lab Note: Broken Rock was within sample.	5-4-5-6 (9)	11.7	13.6	61.3	25.1
		A-2-4, SiSa, brn, Moist, Rec. = 0.9 ft	6-7-6-5 (13)	11.7	3.1	73.7	23.2
10		A-3, Sa, brn, Moist, Rec. = 1.0 ft	6-7-6-5 (13)	8.5	19.3	70.4	10.3
		A-2-4, GrSa, brn, Moist, Rec. = 0.8 ft		9.9	21.4	62.5	16.1
		A-1-b, GrSa, brn, Moist, Rec. = 0.7 ft		5.6	20.7	70.4	8.9
15		A-2-4, GrSa, brn, MTW, Rec. = 0.9 ft, (Visual Classification) Lab Note: Very strong gasoline odor from sample. PID test performed showing 377 ppm.	7-3-3-1 (6)				
20		Field Note:, No Recovery.	9-6-6-6 (12)				
25		A-2-4, SiSa, gry, Moist, Rec. = 0.6 ft, Lab Note: A faint gasoline odor was noticeable in sample.	5-6-6-5 (12)	23.4		78.8	21.2
		A-2-4, Sa, brn, Moist, Rec. = 0.7 ft		27.5		84.4	15.6
30		Hole stopped @ 27.0 ft					
		Remarks: Hole Collapsed at 16.8 ft.					

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
 2. N Values have not been corrected for hammer energy. C is the hammer energy correction factor.
 3. Water level readings have been made at times and under conditions stated. Fluctuations may occur due to other factors than those present at the time measurements were made.

BORING LOG - 2 LYNDON STP 0113(65).GPJ VERMONT AOT.GDT 9/9/15