



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

ROCHESTER
BRF 0162(16)
VT-73 BR-15

Boring No.: B-101

Page No.: 1 of 1

Pin No.: 10C418

Checked By: NSM

Boring Crew: SALISBURY, GARROW
Date Started: 4/11/12 Date Finished: 4/11/12
VTSPG NAD83: N 495621.99 ft E 1542259.40 ft
Station: 3+69.77 Offset: -15.13
Ground Elevation: 1004.1 ft

Casing: WB
Sampler: SS
Type: WB SS
I.D.: 4 in 1.5 in
Hammer Wt: N.A. 140 lb.
Hammer Fall: N.A. 30 in.
Hammer/Rod Type: Auto/AWJ
Rig: CME 45C TRACK CE = 1.34

Groundwater Observations

Date	Depth (ft)	Notes
04/12/12	10.8	AM

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Run (Dip deg.)	Core Rec. % (RQD %)	Drill Rate minutes/ft	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
		A-2-4, SiGrSa, brn, Moist, Rec. = 1.4 ft				2-2-3-3 (5)	14.4	22.1	56.6	21.3
		A-1-b, GrSa, brn, Moist, Rec. = 0.6 ft, NXDC				4-4-3-3 (7)	8.0	39.8	43.1	17.1
5		A-1-b, GrSa, brn, Moist, Rec. = 1.0 ft, NXDC				4-3-3-3 (6)	12.5	35.8	54.6	9.6
		Field Note:, No Recovery				2-3-2-3 (5)				
		Field Note:, No Recovery				R@5.0"				
10		Field Note:, NXDC, Cobbles				5- R@1.0"	28.5			
		Visual Description:, Broken Rock with silty sand, brn, Moist, Rec. = 0.2 ft								
		Field Note:, NXDC, Cobbles								
15		A-1-b, SaGr, brn, Wet, Rec. = 0.4 ft				5-3-3-4 (6)	16.5	48.7	38.8	12.5
		Visual Description:, Broken Rock with sandy gravel, brn, Moist, Rec. = 0.4 ft, NXDC				4-6-13-15 (19)	14.9			
20		A-1-b, SaGr, brn, Moist, Rec. = 1.2 ft				12-12-15-17 (27)	13.3	43.0	42.5	14.5
		Field Note:, NXDC, Gravel								
25		A-1-b, SaGr, brn, Moist, Rec. = 1.4 ft				9-11-13-15 (24)	12.7	42.7	42.4	14.9
		Field Note:, NXDC, Cobbles								
30		A-1-b, SiSaGr, brn, Moist, Rec. = 1.0 ft, Broken Rock was within sample. NXDC.				5-17-7-4 (24)	14.7	45.7	30.9	23.4
		Field Note:, NXDC, Cobbles								
35		Visual Description:, Broken Rock with some weathering, gry, Moist, Rec. = 0.6 ft				24- R@1.0"	9.4			
		35.0 ft - 40.0 ft, Light-greenish-gray to pale-green, chlorite-muscovite-quartz Schist, with minor beds of quartzite. Moderately hard, Unweathered, Fair rock, NXMDC, Closely spaced joints. RMR = 44	1 (65)	96 (42)	4	Top of Bedrock @ 35.0 ft				
					2					
40		40.0 ft - 45.0 ft, Light-greenish-gray to pale-green, chlorite-muscovite-quartz Schist, with minor beds of quartzite. Moderately hard, Unweathered, Fair rock, NXMDC, Closely spaced joints. RMR = 49	2 (65)	96 (78)	4					
					4					
					4					
					4					
45		Hole stopped @ 45.0 ft			4					

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.