



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 MATERIALS & RESEARCH SECTION
 SUBSURFACE INFORMATION

BORING LOG

JAMAICA
 ER-BRF 015-1(23)
 VT-30 BR-19

Boring No.: B-203
 Page No.: 1 of 1
 Pin No.: 11B316
 Checked By: CEE

Boring Crew: GARROW, SALISBURY, PORTER
 Date Started: 12/02/11 Date Finished: 12/03/11
 VTSPG NAD83: N 218603.90 ft E 1564956.10 ft
 Station: _____ Offset: _____
 Ground Elevation: 735.7 ft

Casing: _____ Sampler: _____
 Type: WB SS
 I.D.: 4 in 1.5 in
 Hammer Wt: N.A. 140 lb.
 Hammer Fall: N.A. 30 in.
 Hammer/Rod Type: Auto/AWJ
 Rig: CME 45C SKID CE = 1.33

Groundwater Observations

Date	Depth (ft)	Notes
		Not taken.

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
5		Field Class., Coarse Gravel					
		Field Note., NXDC, Cobbles					
		Field Class., Coarse Gravel					
		Field Class., Sandy Gravel, Old Ground at 15.0 ft.					
		Field Note., NXDC, Cobbles					
15		Field Class., Silty Sand					
		Field Note., NXDC, Cobbles					
20		Field Class., Silty Sand					
		Field Note., NXDC, Cobbles					
25		Hole stopped @ 21.8 ft Possible Bedrock.					
30							
35							

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
 2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
 3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.