



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 MATERIALS & RESEARCH SECTION
 SUBSURFACE INFORMATION

BORING LOG

JAMAICA
 ER-BRF 015-1(23)
 VT-30 BR-19

Boring No.: B-205
 Page No.: 1 of 1
 Pin No.: 11B316
 Checked By: CEE

Boring Crew: GARROW, SALISBURY
 Date Started: 12/14/11 Date Finished: 12/14/11
 VTSPG NAD83: N 218656.30 ft E 1565101.30 ft
 Station: _____ Offset: _____
 Ground Elevation: 730.3 ft

Casing _____ Sampler _____
 Type: WB
 I.D.: 4 in
 Hammer Wt: N.A. N.A.
 Hammer Fall: N.A. N.A.
 Hammer/Rod Type: _____
 Rig: CME 45C SKID CE =

Groundwater Observations		
Date	Depth (ft)	Notes
		Hole Collapsed.
12/14/11		Open to 15 ft.

Depth (ft)	Strata (I)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
		Field Class:, GrSa					
		Field Class:, NXDC, Cobbles					
5		Field Class:, Gr					
		Field Class:, NXDC, Concrete					
10		Field Class:, Sa					
		Field Class:, GrSa					
15		Field Class:, Sa					
		Field Class:, NXDC, Cobbles					
20		Field Class:, Sa					
25		Field Class:, Sa					
30		Hole stopped @ 29.5 ft Possible Bedrock.					
35							

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
 2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
 3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

BORING LOG 2 JAMAICA ER-BRF 015-1(23).GPJ VERMONT AOT.GDT 1/6/12