



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

ROCHESTER
ER-BRF 0162(18)
VT-73 BR-19

Boring No.: B-104
Page No.: 1 of 1
Pin No.: 11C332
Checked By: CEE

Boring Crew: SALISBURY, GARROW
Date Started: 3/27/12 Date Finished: 3/27/12
VTSPG NAD83: N 497038.70 ft E 1558581.80 ft
Station: 14+44 Offset: 9.50
Ground Elevation: 826.7 ft

Casing: WB Sampler: SS
Type: WB SS
I.D.: 4 in 1.5 in
Hammer Wt: N.A. 140 lb.
Hammer Fall: N.A. 30 in.
Hammer/Rod Type: Auto/AWJ
Rig: CME 45C TRACK CE = 1.34

Groundwater Observations

Date	Depth (ft)	Notes
		None Taken.

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Run (Dip deg.)	Core Rec. % (RQD %)	Drill Rate minutes/ft	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
		Asphalt Pavement, 0.0 ft - 1.1 ft								
		Field Note:, NXDC, Gravel								
5		A-1-b, GrSa, brn, Moist, Rec. = 0.8 ft				5-5-4-4 (9)	10.3	34.7	50.9	14.4
		Field Note:, NXDC, Gr Sa Si								
10		A-2-4, GrSa, brn, Moist, Rec. = 0.8 ft				3-2-3-3 (5)	12.9	20.3	61.2	18.5
		Field Note:, NXDC, Gravel								
15		A-1-b, SaGr, brn, Moist, Rec. = 1.0 ft, Broken Rock was within sample.				3-4-14-12 (18)	9.1	57.7	31.8	10.5
		Field Note:, Possible Void								
		Field Note:, NXDC, Possible Silt								
20		Visual Description, Large chunks of Wood with sand & gravel, brn, Moist, Rec. = 0.5 ft				8-3-5-8 (8)				
		Field Note:, NXDC								
25		A-1-a, Weathered Rock with Sand & Gravel, brn, Moist, Rec. = 1.1 ft				10-8-7-17 (15)	8.8	58.5	28.2	13.3
30		25.5 ft - 30.5 ft, Pale green, Quartz-sericite Schist, and chloritoid phyllite with quartzite. Moderately soft to moderately hard, Unweathered, Fair rock, NXMDC, RMR = 54	1 (55)	100 (40)	5 6 8 6 6	Top of Bedrock @ 25.5 ft				
35		30.5 ft - 35.5 ft, Pale green, Quartz-sericite Schist, with quartzite. Moderately hard, Unweathered, Fair rock, NXMDC, Severely weathered vug at 32.7 feet. RMR = 59	2 (55)	100 (64)	5 6 4 5 6					
		Hole stopped @ 35.5 ft								

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

BORING LOG 2 ROCHESTER ER-BRF 0162(18).GPJ VERMONT AOT.GDT 6/1/12