



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

Hartford, VT

191 Bridge 43 N/S

Boring No.: B-217

Page No.: 1 of 2

Pin No.: s12a132

Checked By: ASP

Boring Crew: NTB/Mike Nadeau, MJR

Date Started: 3/25/14 Date Finished: 3/25/14

VTSFG NAD83: N 417515.93 ft E 1683416.13 ft

Station: 250+29.29 Offset: 94.25

Ground Elevation: 555.78 ft

Casing Sampler

Type: Auger/WB SS

I.D.: 4.5 in 2 in

Hammer Wt: 300 lb. 140 lb.

Hammer Fall: N.A. 30 in.

Hammer/Rod Type: Auto

Rig: CME 50 CE = 1.33

Groundwater Observations

Date Depth Notes

03/25/14 10.2 After drilling

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Run (dip deg.)	Core Rec. (ROD %) (ft Value)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
2.5		A-2-4, SaSiGr, Rec. = 1.17 ft, (FILL)			3-7-7-7 (14)	16.8	23.4	47.4	29.2
5.0		A-2-4, SaSiGr, Rec. = 1.83 ft, (FILL)			9-17-17-12 (34)	14.6	17.8	51.3	30.9
5.0		A-1-b, GrSaSi, (FILL)			7.4	48.0	29.5	22.5	
10.0		A-2-4, SaSiGr, Rec. = 1.92 ft			15-14-16-8 (30)	10.8	26.8	41.6	31.6
15.0		A-2-4, GrSaSi, Rec. = 1.08 ft			9-15-18-19 (33)	10.7	37.0	34.5	28.5

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor. CE is an estimated value.
3. Water level readings have been made at times and under conditions stated.
Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.
4. Ground surface elevations indicated on the boring logs were estimated based on the grading plan provided by VDOT.



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

Hartford, VT

191 Bridge 43 N/S

Boring No.: B-217

Page No.: 2 of 2

Pin No.: s12a132

Checked By: ASP

Boring Crew: NTB/Mike Nadeau, MJR

Date Started: 3/25/14 Date Finished: 3/25/14

VTSFG NAD83: N 417515.93 ft E 1683416.13 ft

Station: 250+29.29 Offset: 94.25

Ground Elevation: 555.78 ft

Casing Sampler

Type: Auger/WB SS

I.D.: 4.5 in 2 in

Hammer Wt: 300 lb. 140 lb.

Hammer Fall: N.A. 30 in.

Hammer/Rod Type: Auto

Rig: CME 50 CE = 1.33

Groundwater Observations

Date Depth Notes

03/25/14 10.2 After drilling

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Run (dip deg.)	Core Rec. (ROD %) (ft Value)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
27.5		Rec. = 0.17 ft, 25.0 ft - 27.0 ft			9-11-12-14 (23)				
27.5		Weathered bedrock							
30.0		30.0 ft - 33.0 ft, Gray-green ANDESITE, hard, 70° and 45° joint sets, closely spaced, slight to severe weathering, with quartz boudins.	1	58 (12.5)					
32.5		33.0 ft - 34.5 ft, Green-gray ANDESITE, hard, 45° to 0°, 90° joint sets, closely spaced, rough to smooth, moderately weathered.	2	66 (44)					
35.0		34.5 ft - 36.0 ft, Similar as above, vertical fracture in last 8" piece, very slight weathering.	3	100 (69)					
36.0		Hole stopped @ 36.0 ft							

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor. CE is an estimated value.
3. Water level readings have been made at times and under conditions stated.
Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.
4. Ground surface elevations indicated on the boring logs were estimated based on the grading plan provided by VDOT.



2010 COPY J1145115.GPJ VERMONT_A01.GDT 5/29/14

2010 COPY J1145115.GPJ VERMONT_A01.GDT 5/29/14