



STATE OF VERMONT  
 AGENCY OF TRANSPORTATION  
 MATERIALS & RESEARCH SECTION  
 SUBSURFACE INFORMATION

BORING LOG

COLCHESTER  
 HES NH 5600(14)  
 US2 & US7

Boring No.: B-103  
 Page No.: 1 of 1  
 Pin No.: 12D046  
 Checked By: TDE

Boring Crew: PORTER, GARROW, SALISBURY  
 Date Started: 7/19/12 Date Finished: 7/19/12  
 VTSPG NAD83: N 731191.52 ft E 1462490.85 ft  
 Station: 5+14 Offset: -43.00  
 Ground Elevation: 325.0 ft

Casing H.S.A. Sampler SS  
 Type: H.S.A. SS  
 I.D.: 3.5 in 1.5 in  
 Hammer Wt: N.A. 140 lb.  
 Hammer Fall: N.A. 30 in.  
 Hammer/Rod Type: Auto/AWJ  
 Rig: CME 45C TRACK CE = 1.34

Groundwater Observations

Date	Depth (ft)	Notes
		No water to depth.

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
		A-1-b, SaGr, brn, MTW, Rec. = 1.2 ft	3-5-9-3 (14)	8.7	50.0	33.3	16.7
		A-1-b, GrSa, brn, MTW, Rec. = 1.0 ft	4-2-2-R@2.5"	16.1	36.3	46.6	17.1
5		Hole stopped @ 3.7 ft CNPF-TLOB					
10		Remarks: 1. At Station 5+14: Electrical caution tape was within the 2.0' - 3.7' sample. 2. Moved Hole to 5+19 and advanced casing to 3.7 feet, but could not penetrate further.					
15							
20							
25							

Notes:  
 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.  
 2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.  
 3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

BORING LOG 2 COLCHESTER HES NH 5600(14).GPJ VERMONT AOT.GDT 9/11/12