



STATE OF VERMONT
AGENCY OF TRANSPORTATION
MATERIALS & RESEARCH SECTION
SUBSURFACE INFORMATION

BORING LOG

COLCHESTER
HES NH 5600(14)
US2 & US7

Boring No.: B-125
Page No.: 1 of 1
Pin No.: 12D046
Checked By: TDE

Boring Crew: PORTER, WHITLOCK
Date Started: 7/05/12 Date Finished: 7/05/12
VTSPG NAD83: N 733751.43 ft E 1463264.15 ft
Station: 31+85 Offset: 46.00
Ground Elevation: 333.3 ft

Casing H.S.A. Sampler SS
Type: H.S.A. SS
I.D.: 3.25 in 1.5 in
Hammer Wt: N.A. 140 lb.
Hammer Fall: N.A. 30 in.
Hammer/Rod Type: Auto/AWJ
Rig: CME 45C TRACK CE = 1.34

Groundwater Observations

Date	Depth (ft)	Notes
		Same day drilling.
		No water to depth.

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %	LL %	PI %
5		A-2-4, GrSa, brn, Moist, Rec. = 1.3 ft	2-3-5-4 (8)	14.2	29.8	51.5	18.7		
		A-1-b, SaGr, brn, Moist, Rec. = 1.0 ft	2-3-2-2 (5)	13.3	50.6	38.5	10.9		
		A-2-4, GrSa, brn, Moist, Rec. = 0.8 ft	2-2-4-4 (6)	20.1	29.4	51.1	19.5		
		A-6, SaSiCl, brn, Moist, Rec. = 1.2 ft	5-5-R@2.5"	20.9	12.9	22.7	64.4	38	17
10		Hole stopped @ 7.2 ft CNPF-TLOB							
15									
20									
25									

Notes: 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

BORING LOG 2 COLCHESTER HES NH 5600(14).CPJ VERMONT AOT.GDT 9/11/12