



Boring Crew: <u>M. Blakely, D. Spielvogel</u>		Casing		Sampler		Groundwater		Observations	
Date Started: <u>2/14/12</u>	Date Finished: <u>2/16/12</u>	Type: <u>WB</u>	<u>3 in</u>	<u>SS</u>	<u>1.5 in</u>	Date	Depth (ft)	Notes	
VTSPG NAD83: <u>N 401676.59 ft</u>	<u>E 1510024.93 ft</u>	Hammer Wt: <u>140 lb.</u>	<u>140 lb.</u>			<u>02/14/12</u>	<u>5.8</u>	<u>Estimated</u>	
Station: <u>102+35.00</u>	Offset: <u>17.0 R</u>	Hammer Fall: <u>30 in.</u>	<u>30 in.</u>						
Ground Elevation: <u>525.8 ft</u>		Hammer/Rod Type: <u>Manual/NW</u>							
		Rig: <u>CME 550 ATV</u>	<u>CE = 1</u>						

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
5	(SP)	(SP), <u>f.m.c. SAND</u> , trace silt, loose, brown, wet, Rec. = 0.9 ft	4-4-3 4 (7)				
10	(SP)	(SP), becomes dark brown, Rec. = 0.7 ft	2-2-3 3 (5)				
15	(SP)	(SP), <u>f.m.c. SAND</u> , Some Wood/Organics, loose, brown, wet, Rec. = 0.8 ft	2-3-2 3 (5)				
20	(SP)	(SP), <u>f.m.c. SAND</u> , little f.c. gravel, trace silt, loose, brown, wet, Rec. = 0.7 ft	5-4-4 5 (8)				
25	(SM)	(SM), <u>f. SAND</u> , Some Silt, medium compact, brown, wet, Rec. = 0.5 ft	3-7-5 5 (12)				
30	(SP)	(SP), <u>f.m.c. SAND</u> , trace silt, medium compact, brown, wet, Rec. = 1.0 ft	8-8- 11-9 (19)		1.0	91.5	7.5
35	(SM)	(SM), <u>f. SAND</u> , And SILT, loose, brown, wet, Rec. = 1.4 ft	5-4-5 4 (9)		0.8	59.9	39.3
40	(SM)	(SM), <u>Similar Soil</u> , Rec. = 1.8 ft	3-3-7 15 (10)				
45	(SM)	(SM), <u>f.m.c. SAND</u> , Some Silt, trace f.c. gravel, medium compact, brown, wet, Rec. = 0.2 ft	14-8- 9-13				

Notes:
1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.



Boring Crew: <u>M. Blakely, D. Spielvogel</u>		Casing		Sampler		Groundwater		Observations	
Date Started: <u>2/14/12</u>	Date Finished: <u>2/16/12</u>	Type: <u>WB</u>	<u>3 in</u>	<u>SS</u>	<u>1.5 in</u>	Date	Depth (ft)	Notes	
VTSPG NAD83: <u>N 401676.59 ft</u>	<u>E 1510024.93 ft</u>	Hammer Wt: <u>140 lb.</u>	<u>140 lb.</u>			<u>02/14/12</u>	<u>5.8</u>	<u>Estimated</u>	
Station: <u>102+35.00</u>	Offset: <u>17.0 R</u>	Hammer Fall: <u>30 in.</u>	<u>30 in.</u>						
Ground Elevation: <u>525.8 ft</u>		Hammer/Rod Type: <u>Manual/NW</u>							
		Rig: <u>CME 550 ATV</u>	<u>CE = 1</u>						

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
50	(SM)	(SM), <u>f.m.c. SAND</u> , Some f.c. Gravel, little silt, very compact, brown, wet, Rec. = 0.5 ft	(17)				
55	(GP)	(GP), <u>f.c. GRAVEL</u> , Some f.m.c. Sand, trace silt, very compact, brown, wet, Rec. = 0.5 ft	24-36- 50-3 (R)				
60	(SM)	(SM), <u>f.m.c. SAND</u> , little silt, trace f. gravel, very compact, brown, wet, Rec. = 1.7 ft	22-43- 50-3 (R)				
65	(SM-TILL)	(SM-TILL), <u>f.m.c. SAND</u> , Some f.c. Gravel, little silt, very compact, gray, wet, Rec. = 0.1 ft	100/4" (R)				
70	(SM-TILL)	(SM-TILL), <u>f.m.c. SAND</u> , Some Silt, Some f.c. Gravel, very compact, gray, wet, Rec. = 0.5 ft	150/6" (R)		49.0	24.3	26.7
75	(SM-TILL)	(SM-TILL), <u>Similar Soil</u> , Rec. = 0.2 ft	100/4" (R)				
80	(SM-TILL)	(SM-TILL), <u>Similar Soil</u> , Rec. = 0.3 ft	200/3" (R)				
Hole stopped @ 79.3 ft							
Remarks: Boulders and cobbles were encountered while driving and washing casing below a depth of 49 feet. Boring was advanced open hole below a depth of 69 feet. The description of the classification of the materials is based on USCS criteria that gravel is defined as material retained on a #4 sieve or larger. Laboratory data provided follows AASHTO classification guidelines that gravel is defined as material retained on a #10 sieve or larger.							

Notes:
1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.

2010 COPY 23828_LOSS.SP1 VERMONT AUT.GDT 2/26/13

2010 COPY 23828_LOSS.SP1 VERMONT AUT.GDT 2/26/13