



STATE OF VERMONT
 AGENCY OF TRANSPORTATION
 MATERIALS & RESEARCH SECTION
 SUBSURFACE INFORMATION

BORING LOG

Rutland Bridge Replacement
 23828.1000.32000

Boring No.: HA-102
 Page No.: 1 of 1
 Pin No.: BRF 3000(16)
 Checked By: J. MacGregor

Boring Crew: M. Blakely, D. Spielvogel
 Date Started: 2/22/12 Date Finished: 2/22/12
 VTSPG NAD83: N 401669.21 ft E 1509773.76 ft
 Station: _____ Offset: _____
 Ground Elevation: 531.4 ft

Casing: HA
 Sampler: 3 in
 Type: _____
 I.D.: _____
 Hammer Wt: N.A. N.A.
 Hammer Fall: N.A. N.A.
 Hammer/Rod Type: _____
 Rig: Hand Auger CE = _____

Groundwater Observations		
Date	Depth (ft)	Notes
02/22/12		Not Encountered

Depth (ft)	Strata (1)	CLASSIFICATION OF MATERIALS (Description)	Blows/6" (N Value)	Moisture Content %	Gravel %	Sand %	Fines %
0 - 5		TOPSOIL (SM), f.m.c. SAND, Some Silt, Some f.c. Gravel, brown, moist					
5 - 45		Hole stopped @ 5.0 ft Remarks: Hand Auger HA-102 was attempted two times with 1 foot offset between the two locations. Refusal on cobbles/ c. gravel were encountered at depths of 3.5 feet and at 5.0 feet. Boring log is based upon the deeper attempt. The description of the classification of the materials is based on USCS criteria that gravel is defined as material retained on a #4 sieve or larger.					

Notes:
 1. Stratification lines represent approximate boundary between material types. Transition may be gradual.
 2. N Values have not been corrected for hammer energy. CE is the hammer energy correction factor.
 3. Water level readings have been made at times and under conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the time measurements were made.