

ECONOLITE
44820
115 FAN ON TEMP
DIS. I

SERIES 2
115 VAC
1 AMP
SLO-BLO

RE-THRU
14 ASS

MODEL
200

RING STATUS PHASE STATUS COORD STATUS

1	VEL	0.9	T-N	---	---	---	---	0%	FPCE
	MAX OUT	VEH	R-C	-C-	---	---	---	NIC-001	
	RED REST	FED	---	---	---	---	---	---	---
		PRE	---	---	---	---	---	---	11:36:04

F1 F2 F3 F4 F5 F6
MAIN MENU SUB-MENU PAGE UP PAGE DOWN DISPLAY ADJUST STATUS DISPLAY

YES/ON NO/OFF
1 2 3
4 5 6
7 8 9
REG CALL 0 CLEAR
SPEC FUNC

ECONOLITE

A B C D
+24 VDC 1 AMP SLO-BLO
115 VAC 1 AMP SLO-BLO

TERMINAL TELEMETRY

ASC-8000 S N 6263

RESET AFTER MODIFYING SWITCHES

BI-FAULT MONITOR FAIL
RESET POWER MODE INC PREV. FAIL

MIN. FLASH DUAL SEL. OPTIONS
8 4 2 1 A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

BY ENABLE NO ENABLE IN LATCH 2 3 4 5 8
CM LOG DISABLE END DISABLE WALK DISABLE

SSM SSM
ENABLE 7 8 9 10 11 12

1 AMP
ECONOLITE
CONTROL PRODUCTS, INC.
HAWAII, CA 96708

MODEL
200