

Model 5200  
Wireless Module

SENSOR

**ECONOLITE**

STATUS

**ASC/3-2100**

PORT 3A  
PORT 2  
PORT 1

115 VAC  
1 AMP

SLO-BLO

+24 VDC  
3/4 AMP

ETHERNET  
SERIAL

ENTER

1 2 3  
4 5 6  
7 8 9  
0

MAIN MENU  
BACK  
NEXT PAGE  
NEXT SCREEN  
COPY  
HELP  
STATUS DISPLAY  
NEXT PAGE  
SPEC FUNC  
CLEAR

1 2 3  
4 5 6  
7 8 9  
0

copy  
log  
IN  
CLEAR

**Autoscope**  
Termin Access Point  
ECONOLITE

ETHERNET

1 2 3 4 5 6 7 8 9 10 11 12

1 2 3 4 5 6 7 8 9 10 11 12

RESET AFTER MODIFYING SWITCHES

FAULT MONITOR FAIL  
RESET POWER MODE  
TMC PREV FAIL

MIN. FLASH DUAL SEL. OPTIONS  
ON OFF ON

0421AB ABCDEF  
01 ENABLE 02 LOG DISABLE  
03 ENABLE 04 LOG DISABLE  
05 LATCH 06 WALK DISABLE

1 2 3 4 5 6

7 8 9 10 11 12

SM 123456 SM 789012  
ENABLE

**ECONOLITE**  
CONTROL PRODUCTS, INC.  
Model 200

115 VAC  
1 AMP

SLO-BLO

+24 VDC  
3/4 AMP

Model 200

CONTROLLER

200

200

0

115 VAC