

SENSOR
AMPS

ECONOLITE

RING STATUS: INTERVAL TIMING
PHASE STATUS: 1 2 3 4 5 6 7 8
COORD STATUS

11:22:23 VEH
11:22:23 TEL
11143107

YES/ON NO/OFF

1 2 3
4 5 6
7 8 9
0 CLEAR

PER CALL SPEC FUNC

F1 MAIN MENU F2 SUB-MENU F3 PAGE UP F4 PAGE DOWN F5 DISPLAY ADJUST F6 STATUS DISPLAY

ASC 200

A B C D

TELEMETRY

TERMINAL

120VDC 1 AMP BLO-BLO
115V 1 AMP BLO

RESET AFTER MODIFYING SWITCHES

FAULT MONITOR FAIL

RESET POWER MODE INC. PREV. FAIL

DUAL INDICATION

3:31 DATE

PREVIOUS FAILURE

MIN. FLASH DUAL SEL. OPT IONS

842 TAB ABCDEF

CY ENABLE NO ENABLE WM LATCH L CYM LOG DISABLE DSD DISABLE MUX DISABLE

1 2 3 4 5 6

SSM 1 2 3 4 5 6 SSM 7 8 9 10 11 12

ENABLE ENABLE

1 AMP

ECONOLITE
CONTROL PROCESSING UNIT
MODEL 204

SERIES 2

Optimum MODE

LONG PULSE 1000mA

MED. PR. LG.

174-ASB

SERIES 2

OPTIMUM MODE

LONG PULSE 1000mA

MED. PR. LG.

174-ASB

DPP

CONTROL

200

RED TEL GREEN

204

RED TEL GREEN

ACH AC-CTRL FL RLY ACH

151 152

12 12 12 12

UBE 200

12