

SERIES 2
EB THRU
SERIES 2
MB THRU
SERIES 2
MB THRU
SERIES 2
MB THRU

— RING STATUS — PHASE STATUS — COORD STATUS
INTERVAL TIMING 1 2 3 4 5 6 7 8 STATUS

YES/NO MON/OFF

1 2 3

4 5 6

7 8 9

0 CLEAR

RED CALL SPEC FUNC

F1 MAIN MENU F2 SUB-MENU F3 PAGE UP F4 PAGE DOWN F5 DISPLAY ADJUST F6 STATUS DISPLAY

ECONOLITE

A B C D

24 V 1 AM SLO-BLOW
115 SLO-BLOW

TERMINAL TEMPERATURE

AS 200

RESET AFTER MODIFYING SWITCHES

FAULT MONITOR FAIL

RESET POWER MODE INC PREV FAIL

72.1

MIN FLASH DUAL SEL 8 4 2 1 A B C D E F

BY ENABLE WD ENABLE VM LATCH CVM LOG DISABLE BND DISABLE WALK DISABLE

SSM 1 2 3 4 5 6 7 8 9 10 11 12

1/4 AMP SLOW BLOW

EDI
SSM12LE-PR

EBERLE DESIGN INC., PHOENIX, AZ, 85018

MODEL 200
RED
YEL
GRN

tsc
MODEL 301
RED
YELLOW
GREEN
WEST BOUND THERM. TRAS

MODEL 200
RED
YEL
GRN

NEMA TYPE 3
LC1