

BUS INTERFACE UNIT

- POWER ON
- TRANSMIT
- VALID DATA

M 622

ECONOLITE

SENS: 10-HI 2-LO 1-MID 0-OFF
 FREQ: 10-NORM 2-WLO 1-M 0-H

DET: DET FLT

SENS: 10-HI 2-LO 1-MID 0-OFF
 FREQ: 10-NORM 2-WLO 1-M 0-H

DET: DET FLT

SENS: 10-HI 2-LO 1-MID 0-OFF
 FREQ: 10-NORM 2-WLO 1-M 0-H

DET: DET FLT

LM 622

LINE FREQ. REFERENCE

- +12 VDC 2.5 AMP SLO-BLO
- +24 VDC 2.5 AMP SLO-BLO
- 115 VAC 1.5 AMP SLO-BLO

SENS: 10-HI 2-LO 1-MID 0-OFF
 FREQ: 10-NORM 2-WLO 1-M 0-H

DET: DET FLT

CONTROL PANEL

STATUS DISPLAY

PHASE: 1 2 3 4 5 6 7 8 9 0 1 2

2 RECALL MAX1 9 VEL PER

6 RECALL MAX1 25

CMD SRC HDW FREE

SYS DVC 0% TLM ERR

SYS DVC 0%

PRIORITY: 1 2 3 4 5 6

BUS: 1 2 3

NO STEP

STEP 2

13:02:03

F1 MAIN MENU

F2 NEXT SCREEN

F3 SUB MENU

F4 NEXT DATA

F5 DISPLAY ADJUST

F6 NEXT PAGE

F7 STATUS DISPLAY

F8 HELP

CURSOR

1 2 3

4 5 6

7 8 9

ENTER

TOGGLE

SPEC FUNC 0 CLEAR