

COMMUNICATIONS UNIT

POWER ON
TRANSMIT
VALID DATA

M 6227

ECONOLITE

B.T.U. INDICATOR	L.3	L.4	L.7	L.8	L.11	L.9	L.15	L.13	RECEIVER	TRANSMITTER	DETECTOR SWITCHING
DATA	L.6	L.2	L.0	L.6	L.12	L.10	L.16	L.14	DPH4	DPH6	DPH8

CABINET POWER SUPPLY

POWER SUPPLY

125 VDC 2.5 AMP ECO-REG
15 VAC 1.0 AMP ECO-REG
15 VAC 1.0 AMP ECO-REG
15 VAC 1.0 AMP ECO-REG

CONFLICT
REG FAIL
CVM / MD
24V-1
24V-2
CLEARANCE FAIL
Y-R CLEARANCE
DUAL INDICATION
PORT 1 FAIL
FIELD CHECK FAIL
LOCAL FLASH
DIAGNOSTIC
PGM CARD / CF
TYPE 12
POWER

MMU-16E

RECEIVE
TRANSMIT

1/4 AMP 5.8

PORT 1 SOLC
COAM
RS232C

PORT 3
PORT 2
TERM
TLM

ASC/2S-2100

ECONOLITE CONTROL PRODUCTS, INC.

F1 MAIN MENU
F2 NEXT SCREEN
F3 SUB MENU
F4 NEXT DATA
F5 DISPLAY ADJUST
F6 NEXT PAGE
F7 STATUS DISPLAY
F8 HELP

1 2 3
4 5 6
7 8 9
0 CLEAR

ENTER

SPC FUNC

ENCOM Wireless Modem

RSSI
DATA

RECEIVER
TRANSMITTER

1/4 AMP 5.8

ECONOLITE

J4

157478