


TABLE 1

TERMINAL IDENT.	CONDUCTOR IDENT.
GROUND OR GREEN COLOR	Green insulation for equipment ground only.
W	White or gray insulation for neutral only.
X, Y or Z	Red, black, etc. insulation for hot conductor only.



WARNING: IMPROPER WIRING OF ANY ELECTRICAL DEVICE CAN CAUSE SERIOUS INJURY OR DEATH. THESE WIRING DEVICES SHOULD BE INSTALLED ONLY BY AN ELECTRICIAN OR OTHER QUALIFIED PERSON. NOTICE: CONNECT ONLY COPPER OR COPPER-CLAD WIRE TO THIS DEVICE. SEE REVERSE SIDE FOR WIRING INSTRUCTIONS.

**BUS INTERFACE UNIT**

POWER ON

TRANSMIT

VALID DATA

PORT

**ECONOLITE**

**Autoscope**  
Terra Access Point  
**ECONOLITE**

POWER

MVP 1 2 3 4

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

PORT 1

SELECT 1 2 3 4 5

VALID DATA

XMT

IO

MVP

VIDEO OUTPUT

- B.I.U. DETECTOR #1
- L1
- L2
- L7
- L8
- L5
- L6
- L11
- L12
- L9
- L10
- L15
- L16
- L13
- L14
- PREEMPTOR EVP# 3
- PREEMPTOR EVP# 4
- PREEMPTOR EVP# 5
- PREEMPTOR EVP# 6
- DETECTOR SWITCH MODULE

GRN IN OUT

YEL IN OUT

RED IN OUT

**tsc**

MODEL 304-15

LOAD 1

LOAD 2

**CUBE 204**

GRN IN OUT

YEL IN OUT

RED IN OUT

MODEL SSS-88-I/O